

Luminaire

Code NL4203334K006
Name Everything 55 round adjustable 34° - cornice bianca - 3000K

Measurem.

Code FTS1500199-B
Name Everything 55 round adjustable 34° - cornice bianca - 3000K

Luminaire Flux	457 lm	Luminaire Power	5.5 W	Efficacy	83.091 lm/W	Efficiency	100.00%
Source Flux	457 lm	Maximum value	2282.44 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	80 mm		
Round Luminous Area		Diam.	37 mm	Height	0 mm		
Horizontal Luminous Area		0.001075 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000260 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		04-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		457 lm	
LED Flux=686lm LED Power=5.5W Eff=67% EfcLed=125lm/W EfcLum=83lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(24k)=145000h							
C.I.E.	91 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		


Diam=55mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code NL4203334K006
Name Everything 55 round adjustable 34° - cornice bianca - 3000K

Measurem.


Code FTS1500199-B
Name Everything 55 round adjustable 34° - cornice bianca - 3000K

Luminaire Flux	457 lm	Luminaire Power	5.5 W	Efficacy	83.091 lm/W	Efficiency	100.00%
Source Flux	457 lm	Maximum value	2282.44 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	80 mm		
Round Luminous Area		Diam.	37 mm	Height	0 mm		
Horizontal Luminous Area		0.001075 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000260 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		04-06-2024		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		457 lm	
LED Flux=686lm LED Power=5.5W Eff=67% EfcLed=125lm/W EfcLum=83lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(24k)=145000h							
C.I.E.	91 97 99 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.31	0.62	0.93	1.24	1.54	OC	0.31	0.62	0.93	1.24	1.54
OB	0.31	0.62	0.93	1.24	1.54	OD	0.31	0.62	0.93	1.24	1.54

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1043.07	977.20	611.38	254.19	59.30	22.78	13.12	8.54	4.97	1.49
OB	1043.07	977.20	611.38	254.19	59.30	22.78	13.12	8.54	4.97	1.49
OC	1043.07	977.20	611.38	254.19	59.30	22.78	13.12	8.54	4.97	1.49
OD	1043.07	977.20	611.38	254.19	59.30	22.78	13.12	8.54	4.97	1.49



H[m]	D[m]	Max lux	Med lux	Alpha=17.2°+17.2°	G=0.0
1.00	0.62	1043	625		
2.00	1.24	261	156		
3.00	1.85	116	69		
4.00	2.47	65	39		
5.00	3.09	42	25		