

## Luminaire

Code M0569W83+M109500+M285207

Name CATA TIR BINARIO STABLE WHITE UNITA' OTTICA 3000K DIMM DALI-SWITCHDIM + OTTICA ULTRA NARROW + FILTRO SOFT

## Measurem.

Code FTS1503391

Name CATA TIR BINARIO STABLE WHITE UNITA' OTTICA 3000K DIMM DALI-SWITCHDIM + OTTICA ULTRA NARROW + FILTRO SOFT

Luminaire Flux	1140.70 lm	Luminaire Power	22.00 W	Efficacy	51.85 lm/W	Efficiency	100.00%
Lamps Flux	1140.70 lm	Maximum value	2567.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	130 mm	Height	175 mm		
Round Luminous Area		Diam.	75 mm	Height	50 mm		
Horizontal Luminous Area		0.004418 m2		Emitting area on Plane 180°		0.003750 m2	
Emitting area on Plane 0°		0.003750 m2		Emitting area on Plane 270°		0.003750 m2	
Emitting area on Plane 90°		0.003750 m2		Glare area at 76°		0.004707 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		26-10-2015		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1140.70 lm	
LED Flux=1811,5lm LED Power=17,5W Eff=63% EfcLed=104lm/W EfcLum=52lm/W Ra=90 SDCM=2 L70(6K)=36000h							
C.I.E.	86 95 98 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Diam=130mm




Semipiani C

180.0 ——— 0.0

ULOR 0.12 %

DLOR 99.88 %

RN 0.12 %



## Luminaire

Code M0569W83+M109500+M285207

Name CATA TIR BINARIO STABLE WHITE UNITA' OTTICA 3000K DIMM DALI-SWITCHDIM + OTTICA ULTRA NARROW + FILTRO SOFT

## Measurement

Code FTS1503391


Name CATA TIR BINARIO STABLE WHITE UNITA' OTTICA 3000K DIMM DALI-SWITCHDIM + OTTICA ULTRA NARROW + FILTRO SOFT

Luminaire Flux	1140.70 lm	Luminaire Power	22.00 W	Efficacy	51.85 lm/W	Efficiency	100.00%
Lamps Flux	1140.70 lm	Maximum value	2567.84 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	130 mm	Height	175 mm		
Round Luminous Area		Diam.	75 mm	Height	50 mm		
Horizontal Luminous Area		0.004418 m2		Emitting area on Plane 180°		0.003750 m2	
Emitting area on Plane 0°		0.003750 m2		Emitting area on Plane 270°		0.003750 m2	
Emitting area on Plane 90°		0.003750 m2		Glare area at 76°		0.004707 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		26-10-2015		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1140.70 lm	
LED Flux=1811,5lm LED Power=17,5W Eff=63% EfcLed=104lm/W EfcLum=52lm/W Ra=90 SDCM=2 L70(6K)=36000h							
C.I.E.	86 95 98 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.25	0.50	0.74	0.99	1.24	OC	0.25	0.50	0.74	0.99	1.24
OB	0.25	0.50	0.74	0.99	1.24	OD	0.25	0.50	0.74	0.99	1.24

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2929.14	2593.73	1339.31	516.98	199.82	87.49	47.54	28.30	17.06	13.00
OB	2929.14	2593.73	1339.31	516.98	199.82	87.49	47.54	28.30	17.06	13.00
OC	2929.14	2593.73	1339.31	516.98	199.82	87.49	47.54	28.30	17.06	13.00
OD	2929.14	2593.73	1339.31	516.98	199.82	87.49	47.54	28.30	17.06	13.00



H[m]	D[m]	Max lux	Med lux	Alpha=13.9°+13.9°	G=0.0
1.00	0.50	2929	1772		
2.00	0.99	732	443		
3.00	1.49	325	197		
4.00	1.99	183	111		
5.00	2.48	117	71		