

Luminaire

Code M0569N83+M109600+M281735

Name CATA TIR BINARIO STABLE WHITE UNITA' OTTICA 4000K DIMM DALI-SWITCHDIM + OTTICA SPOT + FILTRO BLU

Measurem.

Code FTS1503516

Name CATA TIR BINARIO STABLE WHITE UNITA' OTTICA 4000K DIMM DALI-SWITCHDIM + OTTICA SPOT + FILTRO BLU

Luminaire Flux	245.23 lm	Luminaire Power	22.00 W	Efficacy	11.15 lm/W	Efficiency	100.00%
Lamps Flux	245.23 lm	Maximum value	4701.40 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	130 mm	Height	176 mm		
Round Luminous Area		Diam.	75 mm	Height	50 mm		
Horizontal Luminous Area		0.004418 m2		Emitting area on Plane 180°		0.003750 m2	
Emitting area on Plane 0°		0.003750 m2		Emitting area on Plane 270°		0.003750 m2	
Emitting area on Plane 90°		0.003750 m2		Glare area at 76°		0.004707 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		09-10-2015		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		245.23 lm	
LED Flux=1943,3lm LED Power=17,5W Eff=13% EfcLed=111lm/W EfcLum=11lm/W L70(6K)=36000h							
C.I.E.	64 80 92 100 100			D DIN 5040	A50		
F UTE	1.00 C			B NBN	BZ 1 / 0.8 / BZ 2 / 1.5 / BZ 3 / 3 / BZ 4		

Diam=130mm



Semipiani C

180.0 ——— 0.0

ULOR 0.30 %

DLOR 99.70 %

RN 0.30 %



