

Luminaire

Code AE32200+AE43001

Name A. SHARPING 2368.DIR.6X4 940 DM VERY WIDE FLOOD + SCREENS 2368 6X4 WHITE


Measurem.

Code FTS1603121

Name A. SHARPING 2368.DIR.6X4 940 DM VERY WIDE FLOOD + SCREENS 2368 6X4 WHITE

Luminaire Flux	5127.98 lm	Luminaire Power	70.00 W	Efficacy	73.26 lm/W	Efficiency	100.00%
Lamps Flux	5127.98 lm	Maximum value	1406.35 cd/klm	Position	C=0.00 G=1.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5127.98 lm	
LED Flux=6987,3lm LED Power=63W Eff=73% EfcLed=111lm/W EfcLum=73lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	97 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

2368mm x 40mm




Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code AE32200+AE43001

Name A. SHARPING 2368.DIR.6X4 940 DM VERY WIDE FLOOD + SCREENS 2368 6X4 WHITE

Measur.

Code FTS1603121


Name A. SHARPING 2368.DIR.6X4 940 DM VERY WIDE FLOOD + SCREENS 2368 6X4 WHITE

Luminaire Flux	5127.98 lm	Luminaire Power	70.00 W	Efficacy	73.26 lm/W	Efficiency	100.00%
Lamps Flux	5127.98 lm	Maximum value	1406.35 cd/klm	Position	C=0.00 G=1.00	CG	Rotosymmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	888 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.032856 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.007949 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		17-07-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5127.98 lm	
LED Flux=6987,3lm LED Power=63W Eff=73% EfcLed=111lm/W EfcLum=73lm/W Ra=90 SDCM=2 L90(20K)=118000h							
C.I.E.	97	99	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.49	0.98	1.47	1.96	2.45	OC	0.49	0.98	1.47	1.96	2.45
OB	0.49	0.98	1.47	1.96	2.45	OD	0.49	0.98	1.47	1.96	2.45

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	7211.70	7160.24	6517.76	4338.89	795.09	138.21	32.38	20.69	13.58	5.07
OB	7211.70	7160.24	6517.76	4338.89	795.09	138.21	32.38	20.69	13.58	5.07
OC	7211.70	7160.24	6517.76	4338.89	795.09	138.21	32.38	20.69	13.58	5.07
OD	7211.70	7160.24	6517.76	4338.89	795.09	138.21	32.38	20.69	13.58	5.07



H[m]	D[m]	Max lux	Med lux	Alpha=26.1°+26.1°	G=0.0 Max non a G
1.00	0.98	7212	4340		
2.00	1.96	1803	1085		
3.00	2.94	801	482		
4.00	3.91	451	271		
5.00	4.89	288	174		