

Luminaire

Code M2885N00+M187300

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 4000K NON DIMMERABILE 2368MM + INDIRETTA LED + OTTICA DARKLIGHT PER LED


Measurement

Code FTS1601376

Name ALGORITMO SYSTEM PIASTRA CABLATA DIRETTA LED 4000K NON DIMMERABILE 2368MM + INDIRETTA LED + OTTICA DARKLIGHT PER LED

Luminaire Flux	8468 lm	Luminaire Power	122.0 W	Efficacy	69.410 lm/W	Efficiency	100.00%
Source Flux	8468 lm	Maximum value	266.67 cd/klm	Position	C=0.00 G=180.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	45 mm	Height	110 mm
Rectangular Luminous Area		Length	2368 mm	Width	32 mm	Height	0 mm
Horizontal Luminous Area		0.075776 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.018332 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		20-06-2016		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		8468 lm	
LED Flux=15855,64lm LED Power=96W Eff=53% EfcLed=165lm/W EfcLum=69lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	70 96 99 39 100			D DIN 5040		D52	
F UTE	0.39 C + 0.61 T			B NBN		BZ 2	

2368mm x 45mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 61.16 %

DLOR 38.84 %

RN 61.16 %

