

Luminaire

Code BH14504+BH16201
Name A.39 SHARP D+IND 2368 LB 34 400K ND NRO + COVER 4X4 OPT. LB WHITE

Measurem.

Code FTS1900493-A
Name A.39 SHARP D+IND 2368 LB 34 400K ND NRO + COVER 4X4 OPT. LB WHITE

Luminaire Flux	9451 lm	Luminaire Power	104.0 W	Efficacy	90.875 lm/W	Efficiency	100.00%
Source Flux	9451 lm	Maximum value	897.94 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		03-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		9451 lm	
LED Flux=12074lm LED Power=85W Eff=78% EfcLed=142lm/W EfcLum=91lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	97 99 100 35 100			D DIN 5040		D62	
F UTE	--			B NBN		BZ 1	

2368mm x 40mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 65.07 %

DLOR 34.93 %

RN 65.07 %



