

Luminaire

Code 0150270A
Name BONTA' CORPO+CIOTOLA VETRO GRIGIO

Measurment

Code FTS2101859
Name BONTA' CORPO+CIOTOLA VETRO GRIGIO

| | | | | | | | |
|---|-----------------|-----------------|---------------|-----------------------------|-----------------|-----------------|-----------------|
| Luminaire Flux | 242 lm | Luminaire Power | 2.4 W | Efficacy | 100.979 lm/W | Efficiency | 100.00% |
| Source Flux | 242 lm | Maximum value | 109.82 cd/klm | Position | C=0.00 G=138.00 | CG | Rotosymmetrical |
| Round Luminaire | | Diam. | 120 mm | Height | 176 mm | | |
| Round Luminous Area | | Diam. | 120 mm | Height | 145 mm | | |
| Horizontal Luminous Area | | 0.011310 m2 | | Emitting area on Plane 180° | | 0.017400 m2 | |
| Emitting area on Plane 0° | | 0.017400 m2 | | Emitting area on Plane 270° | | 0.017400 m2 | |
| Emitting area on Plane 90° | | 0.017400 m2 | | Glare area at 76° | | 0.019619 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Rotosymmetrical | |
| Date | | 24-03-2021 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 242 lm | |
| LED Flux=338lm LED Power=2,5W Eff=72% EfcLed=135lm/W EfcLum=97lm/W CCT=2700 Ra=80 SDCM=3 L70(6K)=50000h | | | | | | | |
| C.I.E. | 11 34 64 36 100 | | | D DIN 5040 | | D12 | |
| F UTE | -- | | | B NBN | | BZ 10 | |

Diam=120mm



Semipiani C

180.0 ——— 0.0

ULOR 63.93 %

DLOR 36.07 %

RN 63.93 %

