

## Luminaire

Code BB00300\_25+M239600  
Name LUCERI TLESS ROUND 25W 930 COMFORT + schermo prismoptico

## Measurement

Code FTS1801367-A  
Name LUCERI TLESS ROUND 25W 930 COMFORT + schermo prismoptico

Luminaire Flux	2299 lm	Luminaire Power	25.0 W	Efficacy	91.960 lm/W	Efficiency	100.00%
Source Flux	2299 lm	Maximum value	701.79 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	211 mm	Height	215 mm		
Round Luminous Area		Diam.	209 mm	Height	0 mm		
Horizontal Luminous Area		0.034307 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.008300 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		25-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2299 lm	
LED Flux=3416lm LED Power=25W Eff=67% EfcLed=137lm/W EfcLum=92lm/W CCT=3000K Ra=90 R9=50 SDCM=1 L70(9k)=50000h							
C.I.E.	72 93 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 2		


Diam=211mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %  
DLOR100.00 %  
RN 0.00 %



## Luminaire

Code BB00300\_25+M239600

Name LUCERI TLESS ROUND 25W 930 COMFORT + schermo prismoptic

## Measurem.

Code FTS1801367-A


Name LUCERI TLESS ROUND 25W 930 COMFORT + schermo prismoptic

Luminaire Flux	2299 lm	Luminaire Power	25.0 W	Efficacy	91.960 lm/W	Efficiency	100.00%
Source Flux	2299 lm	Maximum value	701.79 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	211 mm	Height	215 mm		
Round Luminous Area		Diam.	209 mm	Height	0 mm		
Horizontal Luminous Area		0.034307 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.008300 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		25-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2299 lm	
LED Flux=3416lm LED Power=25W Eff=67% EfcLed=137lm/W EfcLum=92lm/W CCT=3000K Ra=90 R9=50 SDCM=1 L70(9k)=50000h							
C.I.E.	72 93 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 2		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.70	1.40	2.09	2.79	3.49	OC	0.70	1.40	2.09	2.79	3.49
OB	0.70	1.40	2.09	2.79	3.49	OD	0.70	1.40	2.09	2.79	3.49

	Luminous Intensities [ cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1613.42	1600.16	1469.11	1173.27	803.74	434.35	212.75	109.61	45.56	6.60
OB	1613.42	1600.16	1469.11	1173.27	803.74	434.35	212.75	109.61	45.56	6.60
OC	1613.42	1600.16	1469.11	1173.27	803.74	434.35	212.75	109.61	45.56	6.60
OD	1613.42	1600.16	1469.11	1173.27	803.74	434.35	212.75	109.61	45.56	6.60



H[m]	D[m]	Max lux	Med lux	Alpha=34.9°+34.9°	G=0.0
1.00	1.40	1613	761		
2.00	2.79	403	190		
3.00	4.19	179	85		
4.00	5.59	101	48		
5.00	6.98	65	30		