

Luminaire

Code BB01000_25+M239200

Name LUCERI TLESS ROUND 25W 930 MIRROR + schermo trasparente


Measurem.

Code FTS1801241-A

Name LUCERI TLESS ROUND 25W 930 MIRROR + schermo trasparente

Luminaire Flux	2689 lm	Luminaire Power	25.0 W	Efficacy	107.560 lm/W	Efficiency	100.00%
Source Flux	2689 lm	Maximum value	757.51 cd/klm	Position	C=0.00 G=12.00	CG	Rotosymmetrical
Round Luminaire		Diam.	211 mm	Height	215 mm		
Round Luminous Area		Diam.	209 mm	Height	0 mm		
Horizontal Luminous Area		0.034307 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.008300 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		25-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2689 lm	
LED Flux=3416lm LED Power=25W Eff=79% EfcLed=137lm/W EfcLum=108lm/W CCT=3000K Ra=90 R9=50 SDCM=1 L70(9k)=50000h							
C.I.E.	90 100 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Diam=211mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code BB01000_25+M239200

Name LUCERI TLESS ROUND 25W 930 MIRROR + schermo trasparente

Measurem.

Code FTS1801241-A


Name LUCERI TLESS ROUND 25W 930 MIRROR + schermo trasparente

Luminaire Flux	2689 lm	Luminaire Power	25.0 W	Efficacy	107.560 lm/W	Efficiency	100.00%
Source Flux	2689 lm	Maximum value	757.51 cd/klm	Position	C=0.00 G=12.00	CG	Rotosymmetrical
Round Luminaire		Diam.	211 mm	Height	215 mm		
Round Luminous Area		Diam.	209 mm	Height	0 mm		
Horizontal Luminous Area		0.034307 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.008300 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		25-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2689 lm	
LED Flux=3416lm LED Power=25W Eff=79% EfcLed=137lm/W EfcLum=108lm/W CCT=3000K Ra=90 R9=50 SDCM=1 L70(9k)=50000h							
C.I.E.	90 100 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.73	1.47	2.20	2.93	3.66	OC	0.73	1.47	2.20	2.93	3.66
OB	0.73	1.47	2.20	2.93	3.66	OD	0.73	1.47	2.20	2.93	3.66

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1937.08	1914.48	2033.02	1952.39	1152.10	340.39	37.84	6.05	2.91	1.73
OB	1937.08	1914.48	2033.02	1952.39	1152.10	340.39	37.84	6.05	2.91	1.73
OC	1937.08	1914.48	2033.02	1952.39	1152.10	340.39	37.84	6.05	2.91	1.73
OD	1937.08	1914.48	2033.02	1952.39	1152.10	340.39	37.84	6.05	2.91	1.73



H[m]	D[m]	Max lux	Med lux	Alpha=36.2°+36.2°	G=0.0 Max non a G
1.00	1.47	1937	1059		
2.00	2.93	484	265		
3.00	4.40	215	118		
4.00	5.86	121	66		
5.00	7.33	77	42		