

Luminaire

Code 1092010A_x1
Name UNTERLINDEN CHANDELIER RING 3000K OTTONE (singolo emettitore)

Measurem.

Code FTS2300134
Name UNTERLINDEN CHANDELIER RING 3000K OTTONE (singolo emettitore)

Luminaire Flux	368 lm	Luminaire Power	6.8 W	Efficacy	54.069 lm/W	Efficiency	100.00%
Source Flux	368 lm	Maximum value	578.10 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	118 mm	Height	95 mm		
Round Luminous Area		Diam.	45 mm	Height	0 mm		
Horizontal Luminous Area		0.001590 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000385 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		06-06-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		368 lm	
LED Flux=728lm LED Power=6.2W Eff=51% EfcLed=117lm/W EfcLum=54lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(10k)=55000h							
C.I.E.	74 94 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 2		

Diam=118mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code 1092010A_x1
Name UNTERLINDEN CHANDELIER RING 3000K OTTONE (singolo emettitore)

Measurem.


Code FTS2300134
Name UNTERLINDEN CHANDELIER RING 3000K OTTONE (singolo emettitore)

Luminaire Flux	368 lm	Luminaire Power	6.8 W	Efficacy	54.069 lm/W	Efficiency	100.00%
Source Flux	368 lm	Maximum value	578.10 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Round Luminaire		Diam.	118 mm	Height	95 mm		
Round Luminous Area		Diam.	45 mm	Height	0 mm		
Horizontal Luminous Area		0.001590 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000385 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		06-06-2023		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		368 lm	
LED Flux=728lm LED Power=6.2W Eff=51% EfcLed=117lm/W EfcLum=54lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(10k)=55000h							
C.I.E.	74 94 99 100 100			D DIN 5040	A60		
F UTE	1.00 B			B NBN	BZ 2		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.83	1.66	2.48	3.31	4.14	OC	0.83	1.66	2.48	3.31	4.14
OB	0.83	1.66	2.48	3.31	4.14	OD	0.83	1.66	2.48	3.31	4.14

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	212.55	212.06	210.57	199.83	151.57	70.02	31.18	12.94	6.56	0.31
OB	212.55	212.06	210.57	199.83	151.57	70.02	31.18	12.94	6.56	0.31
OC	212.55	212.06	210.57	199.83	151.57	70.02	31.18	12.94	6.56	0.31
OD	212.55	212.06	210.57	199.83	151.57	70.02	31.18	12.94	6.56	0.31



H[m]	D[m]	Max lux	Med lux	Alpha=39.6°+39.6°	G=0.0
1.00	1.66	213	101		
2.00	3.31	53	25		
3.00	4.97	24	11		
4.00	6.62	13	6		
5.00	8.28	9	4		