

Luminaire

Code FT41104
Name OBICE MINI FUNIVIA OUT 930 FL NRO

Measurem.

Code FTS2500079
Name OBICE MINI FUNIVIA OUT 930 FL NRO

Luminaire Flux	586 lm	Luminaire Power	6.5 W	Efficacy	90.154 lm/W	Efficiency	100.00%
Source Flux	586 lm	Maximum value	7447.64 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	70 mm	Height	90 mm		
Round Luminous Area		Diam.	30 mm	Height	0 mm		
Horizontal Luminous Area		0.000707 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000171 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		14-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		586 lm	
LED Flux=732lm LED Power=5.7W Eff=80% EfcLed=129lm/W EfcLum=90lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(24k)=145000h							
C.I.E.	98	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Diam=70mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code FT41104
Name OBICE MINI FUNIVIA OUT 930 FL NRO

Measurem.


Code FTS2500079
Name OBICE MINI FUNIVIA OUT 930 FL NRO

Luminaire Flux	586 lm	Luminaire Power	6.5 W	Efficacy	90.154 lm/W	Efficiency	100.00%
Source Flux	586 lm	Maximum value	7447.64 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Round Luminaire		Diam.	70 mm	Height	90 mm		
Round Luminous Area		Diam.	30 mm	Height	0 mm		
Horizontal Luminous Area		0.000707 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000171 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		14-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		586 lm	
LED Flux=732lm LED Power=5.7W Eff=80% EfcLed=129lm/W EfcLum=90lm/W CCT=3000K Ra=90 R9=50 SDCM=2 L70(24k)=145000h							
C.I.E.	98 100 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.17	0.34	0.51	0.68	0.85	OC	0.17	0.34	0.51	0.68	0.85
OB	0.17	0.34	0.51	0.68	0.85	OD	0.17	0.34	0.51	0.68	0.85

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	4364.32	3615.69	804.12	69.35	17.99	6.96	3.62	1.74	0.68	0.20
OB	4364.32	3615.69	804.12	69.35	17.99	6.96	3.62	1.74	0.68	0.20
OC	4364.32	3615.69	804.12	69.35	17.99	6.96	3.62	1.74	0.68	0.20
OD	4364.32	3615.69	804.12	69.35	17.99	6.96	3.62	1.74	0.68	0.20



H[m]	D[m]	Max lux	Med lux	Alpha=9.6°+9.6°	G=0.0
1.00	0.34	4364	2765		
2.00	0.68	1091	691		
3.00	1.02	485	307		
4.00	1.36	273	173		
5.00	1.69	175	111		