

Luminaire

Code BQ91201
Name VECTOR 40 WALL NO SW 927 FL WHT

Measurement

Code FTS2300019
Name VECTOR 40 WALL NO SW 927 FL WHT

Luminaire Flux	456 lm	Luminaire Power	8.5 W	Efficacy	53.600 lm/W	Efficiency	100.00%
Source Flux	456 lm	Maximum value	5684.10 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	130 mm		
Round Luminous Area		Diam.	33 mm	Height	0 mm		
Horizontal Luminous Area		0.000855 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000207 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		08-11-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		456 lm	
LED Flux=660lm LED Power=6W Eff=69% EfcLed=107lm/W EfcLum=54lm/W CCT=2700K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Diam=40mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code BQ91201
Name VECTOR 40 WALL NO SW 927 FL WHT

Measurem.


Code FTS2300019
Name VECTOR 40 WALL NO SW 927 FL WHT

Luminaire Flux	456 lm	Luminaire Power	8.5 W	Efficacy	53.600 lm/W	Efficiency	100.00%
Source Flux	456 lm	Maximum value	5684.10 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	40 mm	Height	130 mm		
Round Luminous Area		Diam.	33 mm	Height	0 mm		
Horizontal Luminous Area		0.000855 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000207 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		08-11-2022		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		456 lm	
LED Flux=660lm LED Power=6W Eff=69% EfcLed=107lm/W EfcLum=54lm/W CCT=2700K Ra=90 R9=50 SDCM=2 L70(6K)=50000h							
C.I.E.	99	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.18	0.36	0.54	0.72	0.91	OC	0.18	0.36	0.54	0.72	0.91
OB	0.18	0.36	0.54	0.72	0.91	OD	0.18	0.36	0.54	0.72	0.91

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2589.68	2192.77	650.84	142.03	19.51	3.47	1.41	0.41	0.00	0.00
OB	2589.68	2192.77	650.84	142.03	19.51	3.47	1.41	0.41	0.00	0.00
OC	2589.68	2192.77	650.84	142.03	19.51	3.47	1.41	0.41	0.00	0.00
OD	2589.68	2192.77	650.84	142.03	19.51	3.47	1.41	0.41	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=10.3°+10.3°	G=0.0
1.00	0.36	2590	1637		
2.00	0.72	647	409		
3.00	1.09	288	182		
4.00	1.45	162	102		
5.00	1.81	104	65		