

Luminaire


Code 1851030A
Name DREISPITZ 150 S DIF DIR + DIF IND BLK

Measurement

Code FTS2500142
Name DREISPITZ 150 S DIF DIR + DIF IND BLK

Luminaire Flux	5610 lm	Luminaire Power	53.0 W	Efficacy	105.849 lm/W	Efficiency	100.00%
Source Flux	5610 lm	Maximum value	115.80 cd/klm	Position	C=85.00 G=178.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1412 mm	Width	99 mm	Height	104 mm
Rectangular Luminous Area		Length	1400 mm	Width	90 mm	Height	60 mm
Horizontal Luminous Area		0.126000 m2		Emitting area on Plane 180°		0.084000 m2	
Emitting area on Plane 0°		0.084000 m2		Emitting area on Plane 270°		0.005400 m2	
Emitting area on Plane 90°		0.005400 m2		Glare area at 76°		0.111987 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		13-02-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		5610 lm	
LED Flux=7752lm LED Power=45W Eff=72% EfcLed=171lm/W EfcLum=106lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	29 55 79 51 100			D DIN 5040		C11	
F UTE	0.51 J + 0.49 T			B NBN		BZ 7	

1412mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 49.06 %

DLOR 50.94 %

RN 49.06 %

