

Luminaire


Code 1862030A
Name DREISPITZ 120 C/W DIF BLK

Measurem.

Code FTS2500040
Name DREISPITZ 120 C/W DIF BLK

| | | | | | | | |
|---|-----------------|-----------------|---------------|-----------------------------|----------------|--------------------|--------------------|
| Luminaire Flux | 2939 lm | Luminaire Power | 28.0 W | Efficacy | 104.964 lm/W | Efficiency | 100.00% |
| Source Flux | 2939 lm | Maximum value | 175.50 cd/klm | Position | C=40.00 G=1.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1132 mm | Width | 99 mm | Height | 74 mm |
| Rectangular Luminous Area | | Length | 1120 mm | Width | 60 mm | Height | 29 mm |
| Horizontal Luminous Area | | 0.067200 m2 | | Emitting area on Plane 180° | | 0.033600 m2 | |
| Emitting area on Plane 0° | | 0.033600 m2 | | Emitting area on Plane 270° | | 0.001800 m2 | |
| Emitting area on Plane 90° | | 0.001800 m2 | | Glare area at 76° | | 0.048859 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 13-02-2025 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 2939 lm | |
| LED Flux=4060lm LED Power=24W Eff=72% EfcLed=171lm/W EfcLum=105lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h | | | | | | | |
| C.I.E. | 37 65 85 68 100 | | | D DIN 5040 | | B21 | |
| F UTE | 0.68 H + 0.32 T | | | B NBN | | BZ 6 | |

1132mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 31.78 %

DLOR 68.22 %

RN 31.78 %

