

Luminaire


Code 1861000A
Name DREISPITZ 90 C/W DIF SIL

Measurem.

Code FTS2500022
Name DREISPITZ 90 C/W DIF SIL

Luminaire Flux	2391 lm	Luminaire Power	20.0 W	Efficacy	119.550 lm/W	Efficiency	100.00%
Source Flux	2391 lm	Maximum value	181.50 cd/klm	Position	C=35.00 G=2.00	CG	Double Symmetrical
Rectangular Luminaire		Length	822 mm	Width	99 mm	Height	74 mm
Rectangular Luminous Area		Length	810 mm	Width	60 mm	Height	29 mm
Horizontal Luminous Area		0.048600 m2		Emitting area on Plane 180°		0.024300 m2	
Emitting area on Plane 0°		0.024300 m2		Emitting area on Plane 270°		0.001800 m2	
Emitting area on Plane 90°		0.001800 m2		Glare area at 76°		0.035336 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		13-02-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2391 lm	
LED Flux=2953lm LED Power=17W Eff=81% EfcLed=171lm/W EfcLum=120lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	37 65 85 69 100			D DIN 5040	B21		
F UTE	0.69 H + 0.31 T			B NBN	BZ 6		

822mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 30.72 %

DLOR 69.28 %

RN 30.72 %

