

## Luminaire


Code 1692010A  
Name IN-EI MENDORI T EU

## Measurement

Code FTS2600113  
Name IN-EI MENDORI T EU

Luminaire Flux	600 lm	Luminaire Power	8.0 W	Efficacy	75.000 lm/W	Efficiency	100.00%
Source Flux	600 lm	Maximum value	160.91 cd/klm	Position	C=275.00 G=114.00	CG Asymmetrical	
Rectangular Luminaire		Length	500 mm	Width	487 mm	Height	453 mm
Rectangular Luminous Area		Length	500 mm	Width	487 mm	Height	453 mm
Horizontal Luminous Area		0.243500 m <sup>2</sup>		Emitting area on Plane 180°		0.226500 m <sup>2</sup>	
Emitting area on Plane 0°		0.226500 m <sup>2</sup>		Emitting area on Plane 270°		0.220611 m <sup>2</sup>	
Emitting area on Plane 90°		0.220611 m <sup>2</sup>		Glare area at 76°		0.278680 m <sup>2</sup>	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		05-03-2026		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		600 lm	
LED Flux=775lm LED Power=6,5W Eff=77% EfcLed=119lm/W EfcLum=75lm/W CCT=3000K Ra=90 SDCM=2 L70(18k)=109000h							
C.I.E.	25 49 74 47 100			D DIN 5040		C12	
F UTE	0.47 J + 0.53 T			B NBN		BZ 8	

500mm x 487mm



Semipiani C

180.0 — 0.0  
270.0 — 90.0

ULOR 53.48 %

DLOR 46.52 %

RN 53.48 %

