

Luminaire


Code BH15104+BH16204
Name A.39 SHARP D+IND 2368 LB 54 400K DM NRO + COVER 4X4 OPT. LB BLACK

Measurem.

Code FTS1900211-A
Name A.39 SHARP D+IND 2368 LB 54 400K DM NRO + COVER 4X4 OPT. LB BLACK

Luminaire Flux	9487 lm	Luminaire Power	104.0 W	Efficacy	91.221 lm/W	Efficiency	100.00%
Source Flux	9487 lm	Maximum value	503.35 cd/klm	Position	C=0.00 G=0.00	CG	Double Symmetrical
Rectangular Luminaire		Length	2368 mm	Width	40 mm	Height	111 mm
Rectangular Luminous Area		Length	592 mm	Width	37 mm	Height	0 mm
Horizontal Luminous Area		0.021904 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.005299 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		03-03-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		9487 lm	
LED Flux=12074lm LED Power=85W Eff=79% EfcLed=142lm/W EfcLum=91lm/W CCT=4000K Ra=90 R9=50 SDCM=2 L70(17k)=102000h							
C.I.E.	99	100	100	35	100	D DIN 5040	D62
F UTE	--					B NBN	BZ 1

2368mm x 40mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 64.82 %

DLOR 35.18 %

RN 64.82 %

