

Luminaire


Code 1850000A
Name DREISPITZ 120 S DIF SIL

Measurement

Code FTS2500026
Name DREISPITZ 120 S DIF SIL

Luminaire Flux	4931 lm	Luminaire Power	42.0 W	Efficacy	117.405 lm/W	Efficiency	100.00%
Source Flux	4931 lm	Maximum value	115.78 cd/klm	Position	C=90.00 G=177.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1132 mm	Width	99 mm	Height	104 mm
Rectangular Luminous Area		Length	1120 mm	Width	90 mm	Height	60 mm
Horizontal Luminous Area		0.100800 m ²		Emitting area on Plane 180°		0.067200 m ²	
Emitting area on Plane 0°		0.067200 m ²		Emitting area on Plane 270°		0.005400 m ²	
Emitting area on Plane 90°		0.005400 m ²		Glare area at 76°		0.089590 m ²	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		13-02-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4931 lm	
LED Flux=6090lm LED Power=36W Eff=81% EfcLed=171lm/W EfcLum=117lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	28 55 79 51 100			D DIN 5040		C11	
F UTE	0.51 J + 0.49 T			B NBN		BZ 7	

1132mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 48.80 %

DLOR 51.20 %

RN 48.80 %

