

Luminaire


Code 1853000A
Name DREISPITZ 150 S IND DIF SIL

Measurement

Code FTS2500088
Name DREISPITZ 150 S IND DIF SIL

Luminaire Flux	4183 lm	Luminaire Power	33.0 W	Efficacy	126.758 lm/W	Efficiency	100.00%
Source Flux	4183 lm	Maximum value	181.50 cd/klm	Position	C=35.00 G=178.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1412 mm	Width	99 mm	Height	74 mm
Rectangular Luminous Area		Length	1400 mm	Width	60 mm	Height	30 mm
Horizontal Luminous Area		0.084000 m2		Emitting area on Plane 180°		0.042000 m2	
Emitting area on Plane 0°		0.042000 m2		Emitting area on Plane 270°		0.001800 m2	
Emitting area on Plane 90°		0.001800 m2		Glare area at 76°		0.061074 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		30-05-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4183 lm	
LED Flux=5168lm LED Power=30W Eff=81% EfcLed=171lm/W EfcLum=127lm/W CCT=3000K Ra=90 R9=50 SDCM=3 L70(9k)>50000h							
C.I.E.	17 40 69 31 100			D DIN 5040		D12	
F UTE	0.31 J + 0.69 T			B NBN		BZ 10	

1412mm x 99mm



Semipiani C

180.0 — 0.0
270.0 — 90.0

ULOR 69.28 %

DLOR 30.72 %

RN 69.28 %

