

Luminaire

Code 1881W10A
Name SPHERE 35/FUNIVIA 2700K

Measurement

Code FTS2600100
Name SPHERE 35/FUNIVIA 2700K

Luminaire Flux	1740 lm	Luminaire Power	12.6 W	Efficacy	138.661 lm/W	Efficiency	87.01%
Source Flux	2000 lm	Maximum value	76.98 cd/klm	Position	C=0.00 G=76.00	CG	Rotosymmetrical
Round Luminaire		Diam.	350 mm	Height	355 mm		
Round Luminous Area		Diam.	350 mm	Height	320 mm		
Horizontal Luminous Area		0.096211 m2		Emitting area on Plane 180°		0.112000 m2	
Emitting area on Plane 0°		0.112000 m2		Emitting area on Plane 270°		0.112000 m2	
Emitting area on Plane 90°		0.112000 m2		Glare area at 76°		0.131949 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		22-09-2025		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2000 lm	
Lamping=LED 1x13W (E27 opal - 48V) CCT=2700K CRI=80							
C.I.E.	24 48 74 53 87			D DIN 5040		C11	
F UTE	0.46 J + 0.41 T			B NBN		BZ 8	

Diam=350mm



Semipiani C

180.0 ——— 0.0

ULOR 40.56 %

DLOR 46.44 %

RN 46.62 %

