


Luminaire

Code 1550W30A
Name ARRIVAL T NRO 2700K EU

Measurement

Code FTS2600107
Name ARRIVAL T NRO 2700K EU

Luminaire Flux	527 lm	Luminaire Power	17.0 W	Efficacy	31.000 lm/W	Efficiency	100.00%
Source Flux	527 lm	Maximum value	105.76 cd/klm	Position	C=100.00 G=93.00	CG	Asymmetrical
Round Luminaire		Diam.	308 mm	Height	659 mm		
Round Luminous Area		Diam.	308 mm	Height	659 mm		
Horizontal Luminous Area		0.074506 m2		Emitting area on Plane 180°		0.202972 m2	
Emitting area on Plane 0°		0.202972 m2		Emitting area on Plane 270°		0.202972 m2	
Emitting area on Plane 90°		0.202972 m2		Glare area at 76°		0.214967 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		05-03-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		527 lm	
LED Flux=1497lm LED Power=14,4W Eff=35% EfcLed=104lm/W EfcLum=31lm/W CCT=2700K Ra=90 SDCM=3 L70(6k)=36000h							
C.I.E.	17 41 70 49 100			D DIN 5040		C12	
F UTE	0.49 J + 0.51 T			B NBN		BZ 10	



ULOR 51.50 %
DLOR 48.50 %
RN 51.50 %

