**Luminaire**
Code T417600W00
Name FACI 24 INCASSO PARETE LED 3000K CROMO
**Measurem.**
Code FTS0000781
Name FACI 24 INCASSO PARETE LED 3000K CROMO

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Luminaire Flux | 189 lm | Luminaire Power | 7.0 W | Efficacy | 26.996 lm/W | Efficiency | 100.00% |
| Source Flux | 189 lm | Maximum value | 970.98 cd/klm | Position | C=355.00 G=57.00 | CG | Asymmetrical |

| | | | | | |
|---|---|---|---|---|---|
| Rectangular Luminaire | Length | 230 mm | Width | 110 mm | Height | 100 mm |
| Rectangular Luminous Area | Length | 190 mm | Width | 75 mm | Height | 0 mm |


| | | | |
|---|---|---|---|
| Horizontal Luminous Area | 0.014250 m2 | Emitting area on Plane 180° | 0.000000 m2 |
| Emitting area on Plane 0° | 0.000000 m2 | Emitting area on Plane 270° | 0.000000 m2 |
| Emitting area on Plane 90° | 0.000000 m2 | Glare area at 76° | 0.003447 m2 |

| | | | |
|---|---|---|---|
| Coordinate system | CG | Symmetry Type | Asymmetrical |
| Date | 05-10-2012 | Maximum Gamma Angle | 180 |
| Measurement Distance | 0.00 | Measurement Flux | 189 lm |

Led Faci 3000K


| | | | |
|---|---|---|---|
| C.I.E. | 28 67 94 97 100 | D DIN 5040 | A11 |
| F UTE | 0.97 I + 0.03 T | B NBN | BZ 7 / 1 / BZ 6 / 4 / BZ 5 |

230mm x 110mm




Semipiani C

180.0 — 0.0
270.0 — 90.0




ULOR 2.52 %
DLOR 97.48 %
RN 2.52 %

**Luminaire**
Code T417600W00
Name FACI 24 INCASSO PARETE LED 3000K CROMO
**Measurem.**
Code FTS0000781
Name FACI 24 INCASSO PARETE LED 3000K CROMO

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Luminaire Flux | 189 lm | Luminaire Power | 7.0 W | Efficacy | 26.996 lm/W | Efficiency | 100.00% |
| Source Flux | 189 lm | Maximum value | 970.98 cd/klm | Position | C=355.00 G=57.00 | CG | Asymmetrical |

| | | | | | |
|---|---|---|---|---|---|
| Rectangular Luminaire | Length | 230 mm | Width | 110 mm | Height | 100 mm |
| Rectangular Luminous Area | Length | 190 mm | Width | 75 mm | Height | 0 mm |

| | | | |
|---|---|---|---|
| Horizontal Luminous Area | 0.014250 m2 | Emitting area on Plane 180° | 0.000000 m2 |
| Emitting area on Plane 0° | 0.000000 m2 | Emitting area on Plane 270° | 0.000000 m2 |
| Emitting area on Plane 90° | 0.000000 m2 | Glare area at 76° | 0.003447 m2 |

| | | | |
|---|---|---|---|
| Coordinate system | CG | Symmetry Type | Asymmetrical |
| Date | 05-10-2012 | Maximum Gamma Angle | 180 |
| Measurement Distance | 0.00 | Measurement Flux | 189 lm |

Led Faci 3000K


| | | | |
|---|---|---|---|
| C.I.E. | 28 67 94 97 100 | D DIN 5040 | A11 |
| F UTE | 0.97 I + 0.03 T | B NBN | BZ 7 / 1 / BZ 6 / 4 / BZ 5 |

Width at 50.00 % of Max Intensity

| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| OA | 0.90 | 1.79 | 2.69 | 3.59 | 4.48 | OC | 1.62 | 3.25 | 4.87 | 6.49 | 8.11 |
| OB | 1.11 | 2.21 | 3.32 | 4.42 | 5.53 | OD | 1.88 | 3.75 | 5.63 | 7.50 | 9.38 |

Luminous Intensities [ cd/klm]

| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
|---|---|---|---|---|---|---|---|---|---|---|
| OA | 0.39 | 30.81 | 69.67 | 96.76 | 130.32 | 147.20 | 176.64 | 119.33 | 40.63 | 14.33 |
| OB | 0.39 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |
| OC | 0.39 | 0.39 | 0.20 | 0.20 | 0.08 | 0.06 | 0.04 | 0.02 | 0.02 | 0.02 |
| OD | 0.39 | 0.39 | 0.39 | 0.39 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 | 0.00 |




| H[m] | D[m] | Max lux | Med lux | Alpha=33.5°+10.7° G=57.0 |
|---|---|---|---|---|
| 1.00 | 2.00 | 77 | 18 | |
| 2.00 | 4.00 | 19 | 4 | |
| 3.00 | 6.01 | 9 | 2 | |
| 4.00 | 8.01 | 5 | 1 | |
| 5.00 | 10.01 | 3 | 1 | |

| H[m] | D[m] | Max lux | Med lux | Beta=45.6°+41.5° G=0.0 |
|---|---|---|---|---|
| 1.00 | 3.50 | 77 | 18 | |
| 2.00 | 7.00 | 19 | 4 | |
| 3.00 | 10.49 | 9 | 2 | |
| 4.00 | 13.99 | 5 | 1 | |
| 5.00 | 17.49 | 3 | 1 | |