

Luminaire


Code AD40101_W
Name PICTO 125 LED TW TRK 30W FL REG. MANUALE BCO_warm light

Measurem.

Code FTS1603515
Name PICTO 125 LED TW TRK 30W FL REG. MANUALE BCO_warm light

Luminaire Flux	1233.50 lm	Luminaire Power	32.00 W	Efficacy	38.55 lm/W	Efficiency	100.00%
Lamps Flux	1233.50 lm	Maximum value	5376.72 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	125 mm 100 mm	Height Height	300 mm 0 mm		
Horizontal Luminous Area		0.007854 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001900 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		15-02-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1233.50 lm	
LED Flux=2137lm LED Power=27W Eff=57,72% EfcLed=79lm/W EfcLum=39lm/W Ra>93 L70(6K)=50000 h							
C.I.E.	97 98 99 100 100			D DIN 5040		A60	
F UTE	1.00 A			B NBN		BZ 1	

Diam=125mm



Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %

