
Luminaire
Code M251610
Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K SPOT CORNICE NERO / DEFL. NERO
Measurem.
Code FTS1602089
Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K SPOT CORNICE NERO / DEFL. NERO

Luminaire Flux	871.53 lm	Luminaire Power	13.00 W	Efficacy	67.04 lm/W	Efficiency	100.00%
Sources Flux	871.53 lm	Maximum value	4048.68 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical


Round Luminaire	Diam. 80 mm	Height	115 mm
Round Luminous Area	Diam. 50 mm	Height	0 mm
Horizontal Luminous Area	0.001963 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000475 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	26-06-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	871.53 lm

LED Flux=1390lm LED Power=13W Eff=62,7% EfcLed=107lm/W EfcLum=67lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	99 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1



Diam=80mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code M251610
Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K SPOT CORNICE NERO / DEFL. NERO
Measurem.
Code FTS1602089
Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K SPOT CORNICE NERO / DEFL. NERO

Luminaire Flux	871.53 lm	Luminaire Power	13.00 W	Efficacy	67.04 lm/W	Efficiency	100.00%
Sources Flux	871.53 lm	Maximum value	4048.68 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 80 mm	Height	115 mm
Round Luminous Area	Diam. 50 mm	Height	0 mm
Horizontal Luminous Area	0.001963 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000475 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	26-06-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	871.53 lm

LED Flux=1390lm LED Power=13W Eff=62,7% EfcLed=107lm/W EfcLum=67lm/W Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	99 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.21	0.41	0.62	0.83	1.03	OC	0.21	0.41	0.62	0.83	1.03
OB	0.21	0.41	0.62	0.83	1.03	OD	0.21	0.41	0.62	0.83	1.03

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	3528.54	3062.06	1236.51	412.11	83.91	14.69	2.59	0.86	0.47	0.29
OB	3528.54	3062.06	1236.51	412.11	83.91	14.69	2.59	0.86	0.47	0.29
OC	3528.54	3062.06	1236.51	412.11	83.91	14.69	2.59	0.86	0.47	0.29
OD	3528.54	3062.06	1236.51	412.11	83.91	14.69	2.59	0.86	0.47	0.29



H[m]	D[m]	Max lux	Med lux	Alpha=11.7°+11.7° G=0.0
1.00	0.41	3529	2195	
2.00	0.83	882	549	
3.00	1.24	392	244	
4.00	1.65	221	137	
5.00	2.07	141	88	