Luminaire
Code M279010
Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K WIDE FLOOD CORNICE NERO / DEFL. METALLIZZATO
Measurem.
Code FTS1602153
Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K WIDE FLOOD CORNICE NERO / DEFL. METALLIZZATO

Luminaire Flux	892.38 lm	Luminaire Power	13.00 W	Efficacy	68.64 lm/W	Efficiency	100.00%
Sources Flux	892.38 lm	Maximum value	1395.80 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 80 mm	Height	115 mm
Round Luminous Area	Diam. 50 mm	Height	0 mm
Horizontal Luminous Area	0.001963 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000475 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	29-06-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	892.38 lm

LED Flux=1390lm LED Power=13W Eff=64,2% EfcLed=107lm/W EfcLum=69lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	91 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1



Diam=80mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code M279010
Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K WIDE FLOOD CORNICE NERO / DEFL. METALLIZZATO
Measurem.
Code FTS1602153
Name EVERYTHING 80 TONDO TRIM FISSO LED 3000K WIDE FLOOD CORNICE NERO / DEFL. METALLIZZATO

Luminaire Flux	892.38 lm	Luminaire Power	13.00 W	Efficacy	68.64 lm/W	Efficiency	100.00%
Sources Flux	892.38 lm	Maximum value	1395.80 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 80 mm	Height	115 mm
Round Luminous Area	Diam. 50 mm	Height	0 mm
Horizontal Luminous Area	0.001963 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000475 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	29-06-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	892.38 lm

LED Flux=1390lm LED Power=13W Eff=64,2% EfcLed=107lm/W EfcLum=69lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	91 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.43	0.85	1.28	1.70	2.13	OC	0.43	0.85	1.28	1.70	2.13
OB	0.43	0.85	1.28	1.70	2.13	OD	0.43	0.85	1.28	1.70	2.13

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	1245.59	1211.84	912.24	557.74	280.09	97.79	18.04	0.64	0.37	0.31
OB	1245.59	1211.84	912.24	557.74	280.09	97.79	18.04	0.64	0.37	0.31
OC	1245.59	1211.84	912.24	557.74	280.09	97.79	18.04	0.64	0.37	0.31
OD	1245.59	1211.84	912.24	557.74	280.09	97.79	18.04	0.64	0.37	0.31



H[m]	D[m]	Max lux	Med lux	Alpha=23.1°+23.1° G=0.0
1.00	0.85	1246	697	
2.00	1.70	311	174	
3.00	2.56	138	77	
4.00	3.41	78	44	
5.00	4.26	50	28	