
**Luminaire**
Code M279405
Name EVERYTHING 80 TONDO TRIMLESS ORIENTABILE LED 3000K FLOOD DEFL. METALLIZZATO
**Measurem.**
Code FTS1602122
Name EVERYTHING 80 TONDO TRIMLESS ORIENTABILE LED 3000K FLOOD DEFL. METALLIZZATO

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Luminaire Flux | 982.73 lm | Luminaire Power | 13.00 W | Efficacy | 75.59 lm/W | Efficiency | 100.00% |
| Sources Flux | 982.73 lm | Maximum value | 3539.08 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |


| | | | |
|---|---|---|---|
| Round Luminaire | Diam. 80 mm | Height | 115 mm |
| Round Luminous Area | Diam. 50 mm | Height | 0 mm |
| Horizontal Luminous Area | 0.001963 m2 | Emitting area on Plane 180° | 0.000000 m2 |
| Emitting area on Plane 0° | 0.000000 m2 | Emitting area on Plane 270° | 0.000000 m2 |
| Emitting area on Plane 90° | 0.000000 m2 | Glare area at 76° | 0.000475 m2 |
| Coordinate system | CG | Symmetry Type | Rotosymmetrical |
| Date | 26-06-2015 | Maximum Gamma Angle | 180 |
| Measurement Distance | 0.00 | Measurement Flux | 982.73 lm |

LED Flux=1390lm LED Power=13W Eff=70,7% EfcLed=107lm/W EfcLum=76lm/W Ra=90 SDCM=3 L70(6K)=50000h

| | | | |
|---|---|---|---|
| C.I.E. | 96 100 100 100 100 | D DIN 5040 | A60 |
| F UTE | 1.00 A | B NBN | BZ 1 |




Diam=80mm




Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

**Luminaire**
Code M279405
Name EVERYTHING 80 TONDO TRIMLESS ORIENTABILE LED 3000K FLOOD DEFL. METALLIZZATO
**Measurem.**
Code FTS1602122
Name EVERYTHING 80 TONDO TRIMLESS ORIENTABILE LED 3000K FLOOD DEFL. METALLIZZATO

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| Luminaire Flux | 982.73 lm | Luminaire Power | 13.00 W | Efficacy | 75.59 lm/W | Efficiency | 100.00% |
| Sources Flux | 982.73 lm | Maximum value | 3539.08 cd/klm | Position | C=0.00 G=0.00 | CG | Rotosymmetrical |

| | | | |
|---|---|---|---|
| Round Luminaire | Diam. 80 mm | Height | 115 mm |
| Round Luminous Area | Diam. 50 mm | Height | 0 mm |
| Horizontal Luminous Area | 0.001963 m2 | Emitting area on Plane 180° | 0.000000 m2 |
| Emitting area on Plane 0° | 0.000000 m2 | Emitting area on Plane 270° | 0.000000 m2 |
| Emitting area on Plane 90° | 0.000000 m2 | Glare area at 76° | 0.000475 m2 |
| Coordinate system | CG | Symmetry Type | Rotosymmetrical |
| Date | 26-06-2015 | Maximum Gamma Angle | 180 |
| Measurement Distance | 0.00 | Measurement Flux | 982.73 lm |

LED Flux=1390lm LED Power=13W Eff=70,7% EfcLed=107lm/W EfcLum=76lm/W Ra=90 SDCM=3 L70(6K)=50000h


| | | | |
|---|---|---|---|
| C.I.E. | 96 100 100 100 100 | D DIN 5040 | A60 |
| F UTE | 1.00 A | B NBN | BZ 1 |

Width at 50.00 % of Max Intensity

| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
|---|---|---|---|---|---|---|---|---|---|---|---|
| OA | 0.21 | 0.43 | 0.64 | 0.86 | 1.07 | OC | 0.21 | 0.43 | 0.64 | 0.86 | 1.07 |
| OB | 0.21 | 0.43 | 0.64 | 0.86 | 1.07 | OD | 0.21 | 0.43 | 0.64 | 0.86 | 1.07 |

Luminous Intensities [ cd/klm]

| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
|---|---|---|---|---|---|---|---|---|---|---|
| OA | 3477.96 | 3023.54 | 1323.08 | 463.53 | 138.38 | 44.06 | 15.03 | 0.49 | 0.32 | 0.28 |
| OB | 3477.96 | 3023.54 | 1323.08 | 463.53 | 138.38 | 44.06 | 15.03 | 0.49 | 0.32 | 0.28 |
| OC | 3477.96 | 3023.54 | 1323.08 | 463.53 | 138.38 | 44.06 | 15.03 | 0.49 | 0.32 | 0.28 |
| OD | 3477.96 | 3023.54 | 1323.08 | 463.53 | 138.38 | 44.06 | 15.03 | 0.49 | 0.32 | 0.28 |




| H[m] | D[m] | Max lux | Med lux | Alpha=12.1°+12.1° G=0.0 |
|---|---|---|---|---|
| 1.00 | 0.43 | 3478 | 2141 | |
| 2.00 | 0.86 | 869 | 535 | |
| 3.00 | 1.29 | 386 | 238 | |
| 4.00 | 1.72 | 217 | 134 | |
| 5.00 | 2.15 | 139 | 86 | |