

Luminaire


Code AB06358
Name Tagora 80 plafone New led ND Nero/Blu 3000K Very wide flood

Measurem.

Code FTS1603843
Name Tagora 80 plafone New led ND Nero/Blu 3000K Very wide flood

Luminaire Flux	1015.50 lm	Luminaire Power	14.00 W	Efficacy	72.54 lm/W	Efficiency	100.00%
Lamps Flux	1015.50 lm	Maximum value	1449.06 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	335 mm		
Round Luminous Area		Diam.	45 mm	Height	0 mm		
Horizontal Luminous Area		0.001590 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000385 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		19-12-2016		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1015.50 lm	
LED Flux=1489lm LED Power=11,6W Eff=68% EfcLed=128lm/W EfcLum=73lm/W Ra=90 SDCM=3 L70(6K)=60000h							
C.I.E.	97	99	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Diam=80mm




Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code AB06358
Name Tagora 80 plafone New led ND Nero/Blu 3000K Very wide flood

Measurement


Code FTS1603843
Name Tagora 80 plafone New led ND Nero/Blu 3000K Very wide flood

Luminaire Flux	1015.50 lm	Luminaire Power	14.00 W	Efficacy	72.54 lm/W	Efficiency	100.00%
Lamps Flux	1015.50 lm	Maximum value	1449.06 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	80 mm 45 mm	Height Height	335 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.001590 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000385 m2	
Coordinate system Date Measurement Distance		CG 19-12-2016 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1015.50 lm	
LED Flux=1489lm LED Power=11,6W Eff=68% EfcLed=128lm/W EfcLum=73lm/W Ra=90 SDCM=3 L70(6K)=60000h							
C.I.E. F UTE	97 99 100 100 100 --			D DIN 5040 B NBN	A60 BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.50	0.99	1.49	1.99	2.49	OC	0.50	0.99	1.49	1.99	2.49
OB	0.50	0.99	1.49	1.99	2.49	OD	0.50	0.99	1.49	1.99	2.49

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1471.52	1470.44	1336.16	810.95	124.23	24.82	9.38	4.64	2.38	0.85
OB	1471.52	1470.44	1336.16	810.95	124.23	24.82	9.38	4.64	2.38	0.85
OC	1471.52	1470.44	1336.16	810.95	124.23	24.82	9.38	4.64	2.38	0.85
OD	1471.52	1470.44	1336.16	810.95	124.23	24.82	9.38	4.64	2.38	0.85



H[m]	D[m]	Max lux	Med lux	Alpha=26.4°+26.4°	G=0.0
1.00	0.99	1472	835		
2.00	1.99	368	209		
3.00	2.98	164	93		
4.00	3.98	92	52		
5.00	4.97	59	33		