Luminaire
Code M260860
Name EVERYTHING 150 TONDO TRIM FISSO LED WIDE FLOOD CORNICE GRIGIO / DEFL. NERO 3000K
Measurem.
Code FTS1602429
Name EVERYTHING 150 TONDO TRIM FISSO LED WIDE FLOOD CORNICE GRIGIO / DEFL. NERO 3000K


Luminaire Flux	1804.24 lm	Luminaire Power	24.00 W	Efficacy	75.18 lm/W	Efficiency	100.00%
Sources Flux	1804.24 lm	Maximum value	2825.85 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 150 mm	Height	137 mm
Round Luminous Area	Diam. 120 mm	Height	0 mm
Horizontal Luminous Area	0.011310 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002736 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	04-03-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	1804.24 lm

LED Flux=2763lm LED Power=24W Eff=65,3% EfcLed=115lm/W EfcLum=75lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	97 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1


Diam=150mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire
Code M260860
Name EVERYTHING 150 TONDO TRIM FISSO LED WIDE FLOOD CORNICE GRIGIO / DEFL. NERO 3000K
Measurem.
Code FTS1602429
Name EVERYTHING 150 TONDO TRIM FISSO LED WIDE FLOOD CORNICE GRIGIO / DEFL. NERO 3000K

Luminaire Flux	1804.24 lm	Luminaire Power	24.00 W	Efficacy	75.18 lm/W	Efficiency	100.00%
Sources Flux	1804.24 lm	Maximum value	2825.85 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 150 mm	Height	137 mm
Round Luminous Area	Diam. 120 mm	Height	0 mm
Horizontal Luminous Area	0.011310 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002736 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	04-03-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	1804.24 lm

LED Flux=2763lm LED Power=24W Eff=65,3% EfcLed=115lm/W EfcLum=75lm/W Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	97	100	100	100	100	D DIN 5040	A60
F UTE	--					B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.25	0.51	0.76	1.02	1.27	OC	0.25	0.51	0.76	1.02	1.27
OB	0.25	0.51	0.76	1.02	1.27	OD	0.25	0.51	0.76	1.02	1.27

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	5098.52	4666.73	2384.74	944.14	368.00	62.45	7.22	0.63	0.22	0.07
OB	5098.52	4666.73	2384.74	944.14	368.00	62.45	7.22	0.63	0.22	0.07
OC	5098.52	4666.73	2384.74	944.14	368.00	62.45	7.22	0.63	0.22	0.07
OD	5098.52	4666.73	2384.74	944.14	368.00	62.45	7.22	0.63	0.22	0.07



H[m]	D[m]	Max lux	Med lux	Alpha=14.3°+14.3° G=0.0
1.00	0.51	5099	3128	
2.00	1.02	1275	782	
3.00	1.53	567	348	
4.00	2.03	319	195	
5.00	2.54	204	125	