


Luminaire

Code AA50004_DMX255
 Name LOT RIFR.SOSP.TRACK.LED R+W NRO - DMX - CH1 255 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Measurem.

Code FTS1700301
 Name LOT RIFR.SOSP.TRACK.LED R+W NRO - DMX - CH1 255 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	1987.42 lm	Luminaire Power	60.00 W	Efficacy	33.12 lm/W	Efficiency	100.00%
Lamps Flux	1987.42 lm	Maximum value	1304.35 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	185 mm 60 mm	Height Height	80 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.002827 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000684 m2	
Coordinate system Date Measurement Distance		CG 20-03-2017 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1987.42 lm	
Continuous Power=60W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h							
C.I.E. F UTE	91 98 100 100 100 1.00 A			D DIN 5040 B NBN	A60 BZ 1		



Luminaire

Code AA50004_DMX255
 Name LOT RIFR.SOSP.TRACK.LED R+W NRO - DMX - CH1 255 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Measurement


Code FTS1700301
 Name LOT RIFR.SOSP.TRACK.LED R+W NRO - DMX - CH1 255 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	1987.42 lm	Luminaire Power	60.00 W	Efficacy	33.12 lm/W	Efficiency	100.00%
Lamps Flux	1987.42 lm	Maximum value	1304.35 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	185 mm 60 mm	Height Height	80 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.002827 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.000684 m2	
Coordinate system Date Measurement Distance		CG 20-03-2017 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1987.42 lm	
Continuous Power=60W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h							
C.I.E. F UTE	91 98 100 100 100 1.00 A			D DIN 5040 B NBN	A60 BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.48	0.95	1.43	1.91	2.38	OC	0.48	0.95	1.43	1.91	2.38
OB	0.48	0.95	1.43	1.91	2.38	OD	0.48	0.95	1.43	1.91	2.38

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2592.29	2521.07	2081.90	1334.84	576.51	157.88	46.12	19.44	7.78	2.22
OB	2592.29	2521.07	2081.90	1334.84	576.51	157.88	46.12	19.44	7.78	2.22
OC	2592.29	2521.07	2081.90	1334.84	576.51	157.88	46.12	19.44	7.78	2.22
OD	2592.29	2521.07	2081.90	1334.84	576.51	157.88	46.12	19.44	7.78	2.22



H[m]	D[m]	Max lux	Med lux	Alpha=25.5°+25.5°	G=0.0
1.00	0.95	2592	1425		
2.00	1.91	648	356		
3.00	2.86	288	158		
4.00	3.81	162	89		
5.00	4.77	104	57		