Luminaire
Code AA20004_DMX200
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 200 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0
Measurem.
Code FTS1700588
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 200 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0


Luminaire Flux	3820.89 lm	Luminaire Power	55.00 W	Efficacy	69.47 lm/W	Efficiency	100.00%
Lamps Flux	3820.89 lm	Maximum value	1645.78 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	8 mm
Round Luminous Area	Diam. 105 mm	Height	0 mm
Horizontal Luminous Area	0.008659 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002095 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	17-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	3820.89 lm

Continuous Power=55W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h

C.I.E.	93 99 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1


Diam=185mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire
Code AA20004_DMX200
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 200 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0
Measurem.
Code FTS1700588
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 200 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	3820.89 lm	Luminaire Power	55.00 W	Efficacy	69.47 lm/W	Efficiency	100.00%
Lamps Flux	3820.89 lm	Maximum value	1645.78 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	8 mm
Round Luminous Area	Diam. 105 mm	Height	0 mm
Horizontal Luminous Area	0.008659 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002095 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	17-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	3820.89 lm

Continuous Power=55W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h


C.I.E.	93 99 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.38	0.77	1.15	1.54	1.92	OC	0.38	0.77	1.15	1.54	1.92
OB	0.38	0.77	1.15	1.54	1.92	OD	0.38	0.77	1.15	1.54	1.92

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	6288.33	6066.50	4450.12	2377.05	962.53	255.06	80.45	33.21	12.42	3.35
OB	6288.33	6066.50	4450.12	2377.05	962.53	255.06	80.45	33.21	12.42	3.35
OC	6288.33	6066.50	4450.12	2377.05	962.53	255.06	80.45	33.21	12.42	3.35
OD	6288.33	6066.50	4450.12	2377.05	962.53	255.06	80.45	33.21	12.42	3.35



H[m]	D[m]	Max lux	Med lux	Alpha=21.0°+21.0° G=0.0
1.00	0.77	6288	3645	
2.00	1.54	1572	911	
3.00	2.31	699	405	
4.00	3.08	393	228	
5.00	3.85	252	146	