
Luminaire
Code AA20004_DMX100
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 100 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0
Measurem.
Code FTS1700570
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 100 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	2239.59 lm	Luminaire Power	55.00 W	Efficacy	40.72 lm/W	Efficiency	100.00%
Lamps Flux	2239.59 lm	Maximum value	2800.19 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	80 mm
Round Luminous Area	Diam. 105 mm	Height	0 mm
Horizontal Luminous Area	0.008659 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002095 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	16-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	2239.59 lm

Continuous Power=55W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h

C.I.E.	93 98 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1



Diam=185mm

Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code AA20004_DMX100
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 100 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0
Measurem.
Code FTS1700570
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 100 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	2239.59 lm	Luminaire Power	55.00 W	Efficacy	40.72 lm/W	Efficiency	100.00%
Lamps Flux	2239.59 lm	Maximum value	2800.19 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	80 mm
Round Luminous Area	Diam. 105 mm	Height	0 mm
Horizontal Luminous Area	0.008659 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002095 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	16-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	2239.59 lm

Continuous Power=55W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h


C.I.E.	93 98 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.25	0.49	0.74	0.98	1.23	OC	0.25	0.49	0.74	0.98	1.23
OB	0.25	0.49	0.74	0.98	1.23	OD	0.25	0.49	0.74	0.98	1.23

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	6271.28	5256.01	2843.29	1169.03	403.65	123.55	51.99	24.90	11.02	2.90
OB	6271.28	5256.01	2843.29	1169.03	403.65	123.55	51.99	24.90	11.02	2.90
OC	6271.28	5256.01	2843.29	1169.03	403.65	123.55	51.99	24.90	11.02	2.90
OD	6271.28	5256.01	2843.29	1169.03	403.65	123.55	51.99	24.90	11.02	2.90



H[m]	D[m]	Max lux	Med lux	Alpha=13.8°+13.8° G=0.0
1.00	0.49	6271	3716	
2.00	0.98	1568	929	
3.00	1.47	697	413	
4.00	1.96	392	232	
5.00	2.45	251	149	