Luminaire
Code AA20004_DMX0
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 0 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0
Measurem.
Code FTS1700558
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 0 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0


Luminaire Flux	1166.78 lm	Luminaire Power	55.00 W	Efficacy	21.21 lm/W	Efficiency	100.00%
Lamps Flux	1166.78 lm	Maximum value	12608.63 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	80 mm
Round Luminous Area	Diam. 75 mm	Height	0 mm
Horizontal Luminous Area	0.004418 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.001069 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	16-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	1166.78 lm

Continuous Power=55W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h

C.I.E.	92 97 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1


Diam=185mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire
Code AA20004_DMX0
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 0 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0
Measurem.
Code FTS1700558
Name LOT RIFR.RCS.TRIM.LED R+W NRO+NRO - DMX - CH1 0 - CH2 255 - CH3 0 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	1166.78 lm	Luminaire Power	55.00 W	Efficacy	21.21 lm/W	Efficiency	100.00%
Lamps Flux	1166.78 lm	Maximum value	12608.63 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	80 mm
Round Luminous Area	Diam. 75 mm	Height	0 mm
Horizontal Luminous Area	0.004418 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.001069 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	16-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	1166.78 lm

Continuous Power=55W Peak Power=85W CCT=2700K Ra=90 SDCM=2 L70(6K)=50000 h


C.I.E.	92 97 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.04	0.09	0.13	0.18	0.22	OC	0.04	0.09	0.13	0.18	0.22
OB	0.04	0.09	0.13	0.18	0.22	OD	0.04	0.09	0.13	0.18	0.22

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	14711.50	4861.10	1362.01	417.02	142.16	51.18	24.77	26.59	8.15	1.41
OB	14711.50	4861.10	1362.01	417.02	142.16	51.18	24.77	26.59	8.15	1.41
OC	14711.50	4861.10	1362.01	417.02	142.16	51.18	24.77	26.59	8.15	1.41
OD	14711.50	4861.10	1362.01	417.02	142.16	51.18	24.77	26.59	8.15	1.41



H[m]	D[m]	Max lux	Med lux	Alpha=2.5°+2.5°	G=0.0
1.00	0.09	14711	8915		
2.00	0.18	3678	2229		
3.00	0.26	1635	991		
4.00	0.35	919	557		
5.00	0.44	588	357		