
Luminaire
Code AA10001_DMX_R
Name LOT RIFR.RCS.TLES.LED R+W BCO+BCO - DMX - CH1 0 - CH2 0 - CH3 255 - CH4 0 - CH5 0 - CH6 0
Measurem.
Code FTS1700604
Name LOT RIFR.RCS.TLES.LED R+W BCO+BCO - DMX - CH1 0 - CH2 0 - CH3 255 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	224.88 lm	Luminaire Power	55.00 W	Efficacy	4.09 lm/W	Efficiency	100.00%
Lamps Flux	224.88 lm	Maximum value	343.74 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	80 mm
Round Luminous Area	Diam. 185 mm	Height	0 mm
Horizontal Luminous Area	0.026880 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.006503 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	21-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	224.88 lm

Continuous Power=55W Peak Power=85W RED L70(6K)=50000 h

C.I.E. 50 83 97 100 100		D DIN 5040	A30
F UTE 1.00 E		B NBN	BZ 4



Diam=185mm

Semipiani C

180.0 0.0

ULOR 0.01 %
DLOR 99.99 %
RN 0.01 %

Luminaire
Code AA10001_DMX_R
Name LOT RIFR.RCS.TLES.LED R+W BCO+BCO - DMX - CH1 0 - CH2 0 - CH3 255 - CH4 0 - CH5 0 - CH6 0
Measurem.
Code FTS1700604
Name LOT RIFR.RCS.TLES.LED R+W BCO+BCO - DMX - CH1 0 - CH2 0 - CH3 255 - CH4 0 - CH5 0 - CH6 0

Luminaire Flux	224.88 lm	Luminaire Power	55.00 W	Efficacy	4.09 lm/W	Efficiency	100.00%
Lamps Flux	224.88 lm	Maximum value	343.74 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	80 mm
Round Luminous Area	Diam. 185 mm	Height	0 mm
Horizontal Luminous Area	0.026880 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.006503 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	21-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	224.88 lm

Continuous Power=55W Peak Power=85W RED L70(6K)=50000 h


C.I.E.	50 83 97 100 100	D DIN 5040	A30
F UTE	1.00 E	B NBN	BZ 4

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.44	2.88	4.31	5.75	7.19	OC	1.44	2.88	4.31	5.75	7.19
OB	1.44	2.88	4.31	5.75	7.19	OD	1.44	2.88	4.31	5.75	7.19

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	77.30	76.99	73.14	66.05	75.89	59.98	39.02	23.28	11.59	2.09
OB	77.30	76.99	73.14	66.05	75.89	59.98	39.02	23.28	11.59	2.09
OC	77.30	76.99	73.14	66.05	75.89	59.98	39.02	23.28	11.59	2.09
OD	77.30	76.99	73.14	66.05	75.89	59.98	39.02	23.28	11.59	2.09



H[m]	D[m]	Max lux	Med lux	Alpha=55.2°+55.2° G=0.0
1.00	2.88	77	21	
2.00	5.75	19	5	
3.00	8.63	9	2	
4.00	11.50	5	1	
5.00	14.38	3	1	