Luminaire
Code AA40004_DMX_B
Name LOT RIFR.PROJ.TRACK.LED R+W NRO - DMX - CH1 0 - CH2 0 - CH3 0 - CH4 0 - CH5 255 - CH6 0
Measurem.
Code FTS1700323
Name LOT RIFR.PROJ.TRACK.LED R+W NRO - DMX - CH1 0 - CH2 0 - CH3 0 - CH4 0 - CH5 255 - CH6 0


Luminaire Flux	64.05 lm	Luminaire Power	60.00 W	Efficacy	1.07 lm/W	Efficiency	100.00%
Lamps Flux	64.05 lm	Maximum value	350.53 cd/klm	Position	C=0.00 G=11.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	80 mm
Round Luminous Area	Diam. 185 mm	Height	0 mm
Horizontal Luminous Area	0.026880 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.006503 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	20-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	64.05 lm

Continuous Power=60 Peak Power=85W BLUE L70(6K)=50000 h

C.I.E. 51 84 97 100 100		D DIN 5040	A40
F UTE 1.00 D		B NBN	BZ 4


Diam=185mm



Semipiani C

180.0 0.0

ULOR 0.02 %
DLOR 99.98 %
RN 0.02 %



Luminaire
Code AA40004_DMX_B
Name LOT RIFR.PROJ.TRACK.LED R+W NRO - DMX - CH1 0 - CH2 0 - CH3 0 - CH4 0 - CH5 255 - CH6 0
Measurem.
Code FTS1700323
Name LOT RIFR.PROJ.TRACK.LED R+W NRO - DMX - CH1 0 - CH2 0 - CH3 0 - CH4 0 - CH5 255 - CH6 0

Luminaire Flux	64.05 lm	Luminaire Power	60.00 W	Efficacy	1.07 lm/W	Efficiency	100.00%
Lamps Flux	64.05 lm	Maximum value	350.53 cd/klm	Position	C=0.00 G=11.00	CG	Rotosymmetrical

Round Luminaire	Diam. 185 mm	Height	80 mm
Round Luminous Area	Diam. 185 mm	Height	0 mm
Horizontal Luminous Area	0.026880 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.006503 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	20-03-2017	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	64.05 lm

Continuous Power=60 Peak Power=85W BLUE L70(6K)=50000 h


C.I.E.	51 84 97 100 100	D DIN 5040	A40
F UTE	1.00 D	B NBN	BZ 4

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.38	2.76	4.14	5.52	6.90	OC	1.38	2.76	4.14	5.52	6.90
OB	1.38	2.76	4.14	5.52	6.90	OD	1.38	2.76	4.14	5.52	6.90

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	21.83	22.04	22.05	19.63	21.28	17.22	10.75	6.47	3.03	0.63
OB	21.83	22.04	22.05	19.63	21.28	17.22	10.75	6.47	3.03	0.63
OC	21.83	22.04	22.05	19.63	21.28	17.22	10.75	6.47	3.03	0.63
OD	21.83	22.04	22.05	19.63	21.28	17.22	10.75	6.47	3.03	0.63



H[m]	D[m]	Max lux	Med lux	Alpha=54.1°+54.1° G=0.0 Max non a G
1.00	2.76	22	7	
2.00	5.52	5	2	
3.00	8.29	2	1	
4.00	11.05	1	0	
5.00	13.81	1	0	