
Luminaire
Code M265005
Name EVERYTHING 150 QUADRATO TRIMLESS ORIENTABILE LED WIDE FLOOD DEFL. METALIZZATO 3000K
Measurem.
Code FTS1602535
Name EVERYTHING 150 QUADRATO TRIMLESS ORIENTABILE LED WIDE FLOOD DEFL. METALIZZATO 3000K

Luminaire Flux	1892.66 lm	Luminaire Power	24.00 W	Efficacy	78.86 lm/W	Efficiency	100.00%
Sources Flux	1892.66 lm	Maximum value	2083.04 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical


Round Luminaire	Diam. 150 mm	Height	137 mm
Round Luminous Area	Diam. 120 mm	Height	0 mm
Horizontal Luminous Area	0.011310 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002736 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	04-03-2015	Maximum Gamma Angle	90
Measurement Distance	0.00	Measurement Flux	1892.66 lm

LED Flux=2763lm LED Power=24W Eff=68,5% EfcLed=115lm/W EfcLum=79lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	93 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1



Diam=150mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code M265005
Name EVERYTHING 150 QUADRATO TRIMLESS ORIENTABILE LED WIDE FLOOD DEFL. METALIZZATO 3000K
Measurem.
Code FTS1602535
Name EVERYTHING 150 QUADRATO TRIMLESS ORIENTABILE LED WIDE FLOOD DEFL. METALIZZATO 3000K

Luminaire Flux	1892.66 lm	Luminaire Power	24.00 W	Efficacy	78.86 lm/W	Efficiency	100.00%
Sources Flux	1892.66 lm	Maximum value	2083.04 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam.	150 mm	Height	137 mm	
Round Luminous Area	Diam.	120 mm	Height	0 mm	
Horizontal Luminous Area	0.011310 m2		Emitting area on Plane 180°	0.000000 m2	
Emitting area on Plane 0°	0.000000 m2		Emitting area on Plane 270°	0.000000 m2	
Emitting area on Plane 90°	0.000000 m2		Glare area at 76°	0.002736 m2	
Coordinate system	CG		Symmetry Type	Rotosymmetrical	
Date	04-03-2015		Maximum Gamma Angle	90	
Measurement Distance	0.00		Measurement Flux	1892.66 lm	

LED Flux=2763lm LED Power=24W Eff=68,5% EfcLed=115lm/W EfcLum=79lm/W Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	93 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.28	0.57	0.85	1.14	1.42	OC	0.28	0.57	0.85	1.14	1.42
OB	0.28	0.57	0.85	1.14	1.42	OD	0.28	0.57	0.85	1.14	1.42

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	3942.49	3449.00	2040.11	1163.53	524.79	175.28	12.51	0.52	0.16	0.10
OB	3942.49	3449.00	2040.11	1163.53	524.79	175.28	12.51	0.52	0.16	0.10
OC	3942.49	3449.00	2040.11	1163.53	524.79	175.28	12.51	0.52	0.16	0.10
OD	3942.49	3449.00	2040.11	1163.53	524.79	175.28	12.51	0.52	0.16	0.10



H[m]	D[m]	Max lux	Med lux	Alpha=15.9°+15.9° G=0.0
1.00	0.57	3942	2225	
2.00	1.14	986	556	
3.00	1.71	438	247	
4.00	2.28	246	139	
5.00	2.85	158	89	