Luminaire
Code M325925
Name EVERYTHING 80 TONDO TRIM ORIENTABILE LED 2700K WIDE FLOOD CORNICE BIANCO / DEFL. BIANCO
Measurem.
Code FTS1602707
Name EVERYTHING 80 TONDO TRIM ORIENTABILE LED 2700K WIDE FLOOD CORNICE BIANCO / DEFL. BIANCO


Luminaire Flux	985.53 lm	Luminaire Power	13.00 W	Efficacy	75.81 lm/W	Efficiency	100.00%
Sources Flux	985.53 lm	Maximum value	1242.38 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 80 mm	Height	115 mm
Round Luminous Area	Diam. 50 mm	Height	0 mm
Horizontal Luminous Area	0.001963 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000475 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	08-04-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	985.53 lm

LED Flux=1330lm LED Power=13W Eff=74,1% EfcLed=102lm/W EfcLum=76lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	82 94 99 100 100	D DIN 5040	A60
F UTE	1.00 B	B NBN	BZ 1


Diam=80mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire
Code M325925
Name EVERYTHING 80 TONDO TRIM ORIENTABILE LED 2700K WIDE FLOOD CORNICE BIANCO / DEFL. BIANCO
Measurem.
Code FTS1602707
Name EVERYTHING 80 TONDO TRIM ORIENTABILE LED 2700K WIDE FLOOD CORNICE BIANCO / DEFL. BIANCO

Luminaire Flux	985.53 lm	Luminaire Power	13.00 W	Efficacy	75.81 lm/W	Efficiency	100.00%
Sources Flux	985.53 lm	Maximum value	1242.38 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 80 mm	Height	115 mm
Round Luminous Area	Diam. 50 mm	Height	0 mm
Horizontal Luminous Area	0.001963 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000475 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	08-04-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	985.53 lm

LED Flux=1330lm LED Power=13W Eff=74,1% EfcLed=102lm/W EfcLum=76lm/W Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	82 94 99 100 100	D DIN 5040	A60
F UTE	1.00 B	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.43	0.86	1.30	1.73	2.16	OC	0.43	0.86	1.30	1.73	2.16
OB	0.43	0.86	1.30	1.73	2.16	OD	0.43	0.86	1.30	1.73	2.16

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	1224.40	1189.40	906.52	559.45	277.92	105.65	60.56	35.71	17.14	3.94
OB	1224.40	1189.40	906.52	559.45	277.92	105.65	60.56	35.71	17.14	3.94
OC	1224.40	1189.40	906.52	559.45	277.92	105.65	60.56	35.71	17.14	3.94
OD	1224.40	1189.40	906.52	559.45	277.92	105.65	60.56	35.71	17.14	3.94



H[m]	D[m]	Max lux	Med lux	Alpha=23.4°+23.4° G=0.0
1.00	0.86	1224	681	
2.00	1.73	306	170	
3.00	2.59	136	76	
4.00	3.46	77	43	
5.00	4.32	49	27	