

Luminaire

Code M326225

Name EVERYTHING 80 TONDO TRIM ORIENTABILE LED 2700K WIDE FLOOD CORNICE BIANCO / DEFL. NERO


Measurement

Code FTS1602699

Name EVERYTHING 80 TONDO TRIM ORIENTABILE LED 2700K WIDE FLOOD CORNICE BIANCO / DEFL. NERO

Luminaire Flux	630.42 lm	Luminaire Power	13.00 W	Efficacy	48.49 lm/W	Efficiency	100.00%
Sources Flux	630.42 lm	Maximum value	1616.59 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	50 mm	Height	0 mm		
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		29-06-2015		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		630.42 lm	
LED Flux=1330lm LED Power=13W Eff=47,4% EfcLed=102lm/W EfcLum=48lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	96 100 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Diam=80mm




Semipiani C

180.0 — 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code M326225

Name EVERYTHING 80 TONDO TRIM ORIENTABILE LED 2700K WIDE FLOOD CORNICE BIANCO / DEFL. NERO

Measurement

Code FTS1602699


Name EVERYTHING 80 TONDO TRIM ORIENTABILE LED 2700K WIDE FLOOD CORNICE BIANCO / DEFL. NERO

Luminaire Flux	630.42 lm	Luminaire Power	13.00 W	Efficacy	48.49 lm/W	Efficiency	100.00%
Sources Flux	630.42 lm	Maximum value	1616.59 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	80 mm	Height	115 mm		
Round Luminous Area		Diam.	50 mm	Height	0 mm		
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		29-06-2015		Maximum Gamma Angle		90	
Measurement Distance		0.00		Measurement Flux		630.42 lm	
LED Flux=1330lm LED Power=13W Eff=47,4% EfcLed=102lm/W EfcLum=48lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	96 100 100 100 100			D DIN 5040	A60		
F UTE	1.00 A			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.41	0.82	1.23	1.64	2.05	OC	0.41	0.82	1.23	1.64	2.05
OB	0.41	0.82	1.23	1.64	2.05	OD	0.41	0.82	1.23	1.64	2.05

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1019.13	982.68	738.59	425.27	173.15	31.47	3.91	0.95	0.36	0.10
OB	1019.13	982.68	738.59	425.27	173.15	31.47	3.91	0.95	0.36	0.10
OC	1019.13	982.68	738.59	425.27	173.15	31.47	3.91	0.95	0.36	0.10
OD	1019.13	982.68	738.59	425.27	173.15	31.47	3.91	0.95	0.36	0.10



H[m]	D[m]	Max lux	Med lux	Alpha=22.3°+22.3°	G=0.0
1.00	0.82	1019	576		
2.00	1.64	255	144		
3.00	2.46	113	64		
4.00	3.28	64	36		
5.00	4.10	41	23		