
Luminaire
Code M331600
Name EVERYTHING 80 TONDO TRIMLESS FISSO LED 2700K WIDE FLOOD DEFL. METALLIZZATO
Measurem.
Code FTS1602696
Name EVERYTHING 80 TONDO TRIMLESS FISSO LED 2700K WIDE FLOOD DEFL. METALLIZZATO

Luminaire Flux	853.86 lm	Luminaire Power	13.00 W	Efficacy	65.68 lm/W	Efficiency	100.00%
Sources Flux	853.86 lm	Maximum value	1395.80 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical


Round Luminaire	Diam. 80 mm	Height	115 mm
Round Luminous Area	Diam. 50 mm	Height	0 mm
Horizontal Luminous Area	0.001963 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000475 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	29-06-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	853.86 lm

LED Flux=1330lm LED Power=13W Eff=64,2% EfcLed=102lm/W EfcLum=66lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	91 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1



Diam=80mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code M331600
Name EVERYTHING 80 TONDO TRIMLESS FISSO LED 2700K WIDE FLOOD DEFL. METALLIZZATO
Measurem.
Code FTS1602696
Name EVERYTHING 80 TONDO TRIMLESS FISSO LED 2700K WIDE FLOOD DEFL. METALLIZZATO

Luminaire Flux	853.86 lm	Luminaire Power	13.00 W	Efficacy	65.68 lm/W	Efficiency	100.00%
Sources Flux	853.86 lm	Maximum value	1395.80 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 80 mm	Height	115 mm
Round Luminous Area	Diam. 50 mm	Height	0 mm
Horizontal Luminous Area	0.001963 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000475 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	29-06-2015	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	853.86 lm

LED Flux=1330lm LED Power=13W Eff=64,2% EfcLed=102lm/W EfcLum=66lm/W Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	91 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.43	0.85	1.28	1.70	2.13	OC	0.43	0.85	1.28	1.70	2.13
OB	0.43	0.85	1.28	1.70	2.13	OD	0.43	0.85	1.28	1.70	2.13

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	1191.82	1159.53	872.86	533.66	268.00	93.57	17.26	0.61	0.35	0.30
OB	1191.82	1159.53	872.86	533.66	268.00	93.57	17.26	0.61	0.35	0.30
OC	1191.82	1159.53	872.86	533.66	268.00	93.57	17.26	0.61	0.35	0.30
OD	1191.82	1159.53	872.86	533.66	268.00	93.57	17.26	0.61	0.35	0.30



H[m]	D[m]	Max lux	Med lux	Alpha=23.1°+23.1° G=0.0
1.00	0.85	1192	667	
2.00	1.70	298	167	
3.00	2.56	132	74	
4.00	3.41	74	42	
5.00	4.26	48	27	