


Luminaire

Code AE15000+AE41001
 Name A. SHARPING 1184.DIR+IND 3X4 930 DM FLOOD + SCREENS 1184 3X4 WHITE

Measur.

Code FTS1603098
 Name A. SHARPING 1184.DIR+IND 3X4 930 DM FLOOD + SCREENS 1184 3X4 WHITE

| | | | | | | | |
|---|-------------------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 4948.14 lm | Luminaire Power | 64.00 W | Efficacy | 77.31 lm/W | Efficiency | 100.00% |
| Lamps Flux | 4948.14 lm | Maximum value | 2769.10 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1184 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 444 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.016428 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.003974 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 21-02-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 4948.14 lm | |
| LED Flux=6479,35lm LED Power=55W Eff=76% EfcLed=118lm/W EfcLum=77lm/W Ra=90 SDCM=2 L90(20K)=118000h | | | | | | | |
| C.I.E. | 99 100 100 50 100 | | | D DIN 5040 | | C61 | |
| F UTE | -- | | | B NBN | | BZ 1 | |



Luminaire

Code AE15000+AE41001
 Name A. SHARPING 1184.DIR+IND 3X4 930 DM FLOOD + SCREENS 1184 3X4 WHITE

Measurment.


Code FTS1603098
 Name A. SHARPING 1184.DIR+IND 3X4 930 DM FLOOD + SCREENS 1184 3X4 WHITE

| | | | | | | | |
|---|------------|-----------------|----------------|-----------------------------|---------------|--------------------|--------------------|
| Luminaire Flux | 4948.14 lm | Luminaire Power | 64.00 W | Efficacy | 77.31 lm/W | Efficiency | 100.00% |
| Lamps Flux | 4948.14 lm | Maximum value | 2769.10 cd/klm | Position | C=0.00 G=0.00 | CG | Double Symmetrical |
| Rectangular Luminaire | | Length | 1184 mm | Width | 40 mm | Height | 111 mm |
| Rectangular Luminous Area | | Length | 444 mm | Width | 37 mm | Height | 0 mm |
| Horizontal Luminous Area | | 0.016428 m2 | | Emitting area on Plane 180° | | 0.000000 m2 | |
| Emitting area on Plane 0° | | 0.000000 m2 | | Emitting area on Plane 270° | | 0.000000 m2 | |
| Emitting area on Plane 90° | | 0.000000 m2 | | Glare area at 76° | | 0.003974 m2 | |
| Coordinate system | | CG | | Symmetry Type | | Double Symmetrical | |
| Date | | 21-02-2017 | | Maximum Gamma Angle | | 180 | |
| Measurement Distance | | 0.00 | | Measurement Flux | | 4948.14 lm | |
| LED Flux=6479,35lm LED Power=55W Eff=76% EfcLed=118lm/W EfcLum=77lm/W Ra=90 SDCM=2 L90(20K)=118000h | | | | | | | |
| C.I.E. | 99 | 100 | 100 | 50 | 100 | D DIN 5040 | C61 |
| F UTE | -- | | | | | B NBN | BZ 1 |

Width at 50.00 % of Max Intensity

| | | | | | | | | | | | |
|------|------|------|------|------|------|------|------|------|------|------|------|
| H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 | H[m] | 1.00 | 2.00 | 3.00 | 4.00 | 5.00 |
| OA | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 | OC | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 |
| OB | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 | OD | 0.18 | 0.35 | 0.53 | 0.70 | 0.88 |

| | | | | | | | | | | |
|----|--------------------------------|----------|---------|--------|-------|-------|------|------|------|------|
| | Luminous Intensities [cd/klm] | | | | | | | | | |
| | 0 | 5 | 15 | 25 | 35 | 45 | 55 | 65 | 75 | 85 |
| OA | 13701.90 | 11660.37 | 3597.36 | 983.58 | 61.72 | 17.41 | 6.05 | 3.88 | 2.75 | 1.30 |
| OB | 13701.90 | 11660.37 | 3597.36 | 983.58 | 61.72 | 17.41 | 6.05 | 3.88 | 2.75 | 1.30 |
| OC | 13701.90 | 11660.37 | 3597.36 | 983.58 | 61.72 | 17.41 | 6.05 | 3.88 | 2.75 | 1.30 |
| OD | 13701.90 | 11660.37 | 3597.36 | 983.58 | 61.72 | 17.41 | 6.05 | 3.88 | 2.75 | 1.30 |



| H[m] | D[m] | Max lux | Med lux | Alpha=10.0°+10.0° | G=0.0 |
|------|------|---------|---------|-------------------|-------|
| 1.00 | 0.35 | 13702 | 8737 | | |
| 2.00 | 0.70 | 3425 | 2184 | | |
| 3.00 | 1.05 | 1522 | 971 | | |
| 4.00 | 1.41 | 856 | 546 | | |
| 5.00 | 1.76 | 548 | 349 | | |

| H[m] | D[m] | Max lux | Med lux | Beta=10.0°+10.0° | G=0.0 |
|------|------|---------|---------|------------------|-------|
| 1.00 | 0.35 | 13702 | 8737 | | |
| 2.00 | 0.70 | 3425 | 2184 | | |
| 3.00 | 1.05 | 1522 | 971 | | |
| 4.00 | 1.41 | 856 | 546 | | |
| 5.00 | 1.76 | 548 | 349 | | |