
Luminaire
Code M327500
Name EVERYTHING 80 QUADRATO TRIMLESS FISSO LED 2700K SPOT DEFL. BIANCO
Measurem.
Code FTS1602726
Name EVERYTHING 80 QUADRATO TRIMLESS FISSO LED 2700K SPOT DEFL. BIANCO

Luminaire Flux	992.20 lm	Luminaire Power	13.00 W	Efficacy	76.32 lm/W	Efficiency	100.00%
Sources Flux	992.20 lm	Maximum value	3592.99 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Rectangular Luminaire	Length	80 mm	Width	80 mm	Height 115 mm
Round Luminous Area	Diam.	50 mm	Height	0 mm	
Horizontal Luminous Area	0.001963 m2		Emitting area on Plane 180°	0.000000 m2	
Emitting area on Plane 0°	0.000000 m2		Emitting area on Plane 270°	0.000000 m2	
Emitting area on Plane 90°	0.000000 m2		Glare area at 76°	0.000475 m2	
Coordinate system	CG		Symmetry Type	Rotosymmetrical	
Date	08-04-2015		Maximum Gamma Angle	90	
Measurement Distance	0.00		Measurement Flux	992.20 lm	

LED Flux=1330lm LED Power=13W Eff=74,6% EfcLed=102lm/W EfcLum=76lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	94 99 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1



80mm x 80mm

Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code M327500
Name EVERYTHING 80 QUADRATO TRIMLESS FISSO LED 2700K SPOT DEFL. BIANCO
Measurem.
Code FTS1602726
Name EVERYTHING 80 QUADRATO TRIMLESS FISSO LED 2700K SPOT DEFL. BIANCO

Luminaire Flux	992.20 lm	Luminaire Power	13.00 W	Efficacy	76.32 lm/W	Efficiency	100.00%
Sources Flux	992.20 lm	Maximum value	3592.99 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Rectangular Luminaire	Length	80 mm	Width	80 mm	Height 115 mm
Round Luminous Area	Diam.	50 mm	Height	0 mm	
Horizontal Luminous Area	0.001963 m2		Emitting area on Plane 180°	0.000000 m2	
Emitting area on Plane 0°	0.000000 m2		Emitting area on Plane 270°	0.000000 m2	
Emitting area on Plane 90°	0.000000 m2		Glare area at 76°	0.000475 m2	
Coordinate system	CG		Symmetry Type	Rotosymmetrical	
Date	08-04-2015		Maximum Gamma Angle	90	
Measurement Distance	0.00		Measurement Flux	992.20 lm	

LED Flux=1330lm LED Power=13W Eff=74,6% EfcLed=102lm/W EfcLum=76lm/W Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	94 99 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.21	0.41	0.62	0.82	1.03	OC	0.21	0.41	0.62	0.82	1.03
OB	0.21	0.41	0.62	0.82	1.03	OD	0.21	0.41	0.62	0.82	1.03

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	3564.97	3080.82	1242.65	462.62	153.16	43.16	21.56	10.85	2.95	0.00
OB	3564.97	3080.82	1242.65	462.62	153.16	43.16	21.56	10.85	2.95	0.00
OC	3564.97	3080.82	1242.65	462.62	153.16	43.16	21.56	10.85	2.95	0.00
OD	3564.97	3080.82	1242.65	462.62	153.16	43.16	21.56	10.85	2.95	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=11.6°+11.6° G=0.0
1.00	0.41	3565	2214	
2.00	0.82	891	553	
3.00	1.24	396	246	
4.00	1.65	223	138	
5.00	2.06	143	89	