

Luminaire


Code M330305
Name EVERYTHING 105 QUADRATO TRIMLESS ORIENTABILE LED 2700K FLOOD DEFL. METALLIZZATO

Measurement

Code FTS1602583
Name EVERYTHING 105 QUADRATO TRIMLESS ORIENTABILE LED 2700K FLOOD DEFL. METALLIZZATO

Luminaire Flux	674.31 lm	Luminaire Power	13.00 W	Efficacy	51.87 lm/W	Efficiency	100.00%
Sources Flux	674.31 lm	Maximum value	1723.54 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Rectangular Luminaire Round Luminous Area		Length Diam.	105 mm 50 mm	Width Height	105 mm 0 mm	Height	115 mm
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		06-07-2015		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		674.31 lm	
LED Flux=1330lm LED Power=13W Eff=50,7% EfcLed=102lm/W EfcLum=52lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	95 100 100 100 100			D DIN 5040		A60	
F UTE	1.00 A			B NBN		BZ 1	


105mm x 105mm



Semipiani C

180.0 ——— 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire

Code M330305
Name EVERYTHING 105 QUADRATO TRIMLESS ORIENTABILE LED 2700K FLOOD DEFL. METALLIZZATO

Measurem.


Code FTS1602583
Name EVERYTHING 105 QUADRATO TRIMLESS ORIENTABILE LED 2700K FLOOD DEFL. METALLIZZATO

Luminaire Flux	674.31 lm	Luminaire Power	13.00 W	Efficacy	51.87 lm/W	Efficiency	100.00%
Sources Flux	674.31 lm	Maximum value	1723.54 cd/klm	Position	C=0.00 G=0.00	CG Rotosymmetrical	
Rectangular Luminaire Round Luminous Area		Length Diam.	105 mm 50 mm	Width Height	105 mm 0 mm	Height	115 mm
Horizontal Luminous Area		0.001963 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000475 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		06-07-2015		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		674.31 lm	
LED Flux=1330lm LED Power=13W Eff=50,7% EfcLed=102lm/W EfcLum=52lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E. F UTE	95 100 100 100 100 1.00 A			D DIN 5040 B NBN	A60 BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.38	0.76	1.14	1.51	1.89	OC	0.38	0.76	1.14	1.51	1.89
OB	0.38	0.76	1.14	1.51	1.89	OD	0.38	0.76	1.14	1.51	1.89

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1162.20	1095.13	775.52	447.93	181.71	44.78	2.42	0.50	0.34	0.25
OB	1162.20	1095.13	775.52	447.93	181.71	44.78	2.42	0.50	0.34	0.25
OC	1162.20	1095.13	775.52	447.93	181.71	44.78	2.42	0.50	0.34	0.25
OD	1162.20	1095.13	775.52	447.93	181.71	44.78	2.42	0.50	0.34	0.25



H[m]	D[m]	Max lux	Med lux	Alpha=20.7°+20.7°	G=0.0
1.00	0.76	1162	657		
2.00	1.51	291	164		
3.00	2.27	129	73		
4.00	3.03	73	41		
5.00	3.79	46	26		