
Luminaire
Code M323865
Name EVERYTHING 150 TONDO TRIM ORIENTABILE LED WIDE FLOOD CORNICE GRIGIO / DEFL. METALIZZATO 2700K
Measurem.
Code FTS1602818
Name EVERYTHING 150 TONDO TRIM ORIENTABILE LED WIDE FLOOD CORNICE GRIGIO / DEFL. METALIZZATO 2700K

Luminaire Flux	1811.83 lm	Luminaire Power	24.00 W	Efficacy	75.49 lm/W	Efficiency	100.00%
Sources Flux	1811.83 lm	Maximum value	2083.04 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical


Round Luminaire	Diam. 150 mm	Height	137 mm
Round Luminous Area	Diam. 120 mm	Height	0 mm
Horizontal Luminous Area	0.011310 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002736 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	04-03-2015	Maximum Gamma Angle	90
Measurement Distance	0.00	Measurement Flux	1811.83 lm

LED Flux=2645lm LED Power=24W Eff=68,5% EfcLed=110lm/W EfcLum=75lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	93 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1



Diam=150mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code M323865
Name EVERYTHING 150 TONDO TRIM ORIENTABILE LED WIDE FLOOD CORNICE GRIGIO / DEFL. METALIZZATO 2700K
Measurem.
Code FTS1602818
Name EVERYTHING 150 TONDO TRIM ORIENTABILE LED WIDE FLOOD CORNICE GRIGIO / DEFL. METALIZZATO 2700K

Luminaire Flux	1811.83 lm	Luminaire Power	24.00 W	Efficacy	75.49 lm/W	Efficiency	100.00%
Sources Flux	1811.83 lm	Maximum value	2083.04 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam.	150 mm	Height	137 mm	
Round Luminous Area	Diam.	120 mm	Height	0 mm	
Horizontal Luminous Area	0.011310 m2		Emitting area on Plane 180°	0.000000 m2	
Emitting area on Plane 0°	0.000000 m2		Emitting area on Plane 270°	0.000000 m2	
Emitting area on Plane 90°	0.000000 m2		Glare area at 76°	0.002736 m2	
Coordinate system	CG		Symmetry Type	Rotosymmetrical	
Date	04-03-2015		Maximum Gamma Angle	90	
Measurement Distance	0.00		Measurement Flux	1811.83 lm	

LED Flux=2645lm LED Power=24W Eff=68,5% EfcLed=110lm/W EfcLum=75lm/W Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	93 100 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.28	0.57	0.85	1.14	1.42	OC	0.28	0.57	0.85	1.14	1.42
OB	0.28	0.57	0.85	1.14	1.42	OD	0.28	0.57	0.85	1.14	1.42

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	3774.12	3301.70	1952.99	1113.84	502.37	167.79	11.97	0.50	0.16	0.10
OB	3774.12	3301.70	1952.99	1113.84	502.37	167.79	11.97	0.50	0.16	0.10
OC	3774.12	3301.70	1952.99	1113.84	502.37	167.79	11.97	0.50	0.16	0.10
OD	3774.12	3301.70	1952.99	1113.84	502.37	167.79	11.97	0.50	0.16	0.10



H[m]	D[m]	Max lux	Med lux	Alpha=15.9°+15.9° G=0.0
1.00	0.57	3774	2130	
2.00	1.14	944	533	
3.00	1.71	419	237	
4.00	2.28	236	133	
5.00	2.85	151	85	