Luminaire
Code M325400
Name EVERYTHING 150 QUADRATO TRIMLESS FISSO LED FLOOD DEFL. METALIZZATO 2700K
Measurem.
Code FTS1602601
Name EVERYTHING 150 QUADRATO TRIMLESS FISSO LED FLOOD DEFL. METALIZZATO 2700K


Luminaire Flux	2327.60 lm	Luminaire Power	24.00 W	Efficacy	96.98 lm/W	Efficiency	100.00%
Sources Flux	2327.60 lm	Maximum value	5207.68 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 150 mm	Height	137 mm
Round Luminous Area	Diam. 120 mm	Height	0 mm
Horizontal Luminous Area	0.011310 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.002736 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	11-03-2015	Maximum Gamma Angle	90
Measurement Distance	0.00	Measurement Flux	2327.60 lm

LED Flux=2645lm LED Power=24W Eff=88% EfcLed=110lm/W EfcLum=97lm/W Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	99 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1


Diam=150mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %



Luminaire
Code M325400
Name EVERYTHING 150 QUADRATO TRIMLESS FISSO LED FLOOD DEFL. METALIZZATO 2700K
Measurem.
Code FTS1602601
Name EVERYTHING 150 QUADRATO TRIMLESS FISSO LED FLOOD DEFL. METALIZZATO 2700K

Luminaire Flux	2327.60 lm	Luminaire Power	24.00 W	Efficacy	96.98 lm/W	Efficiency	100.00%
Sources Flux	2327.60 lm	Maximum value	5207.68 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam.	150 mm	Height	137 mm	
Round Luminous Area	Diam.	120 mm	Height	0 mm	
Horizontal Luminous Area	0.011310 m2		Emitting area on Plane 180°	0.000000 m2	
Emitting area on Plane 0°	0.000000 m2		Emitting area on Plane 270°	0.000000 m2	
Emitting area on Plane 90°	0.000000 m2		Glare area at 76°	0.002736 m2	
Coordinate system	CG		Symmetry Type	Rotosymmetrical	
Date	11-03-2015		Maximum Gamma Angle	90	
Measurement Distance	0.00		Measurement Flux	2327.60 lm	

LED Flux=2645lm LED Power=24W Eff=88% EfcLed=110lm/W EfcLum=97lm/W Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	99 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.17	0.33	0.50	0.66	0.83	OC	0.17	0.33	0.50	0.66	0.83
OB	0.17	0.33	0.50	0.66	0.83	OD	0.17	0.33	0.50	0.66	0.83

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	12121.39	9776.78	2629.03	968.35	424.26	32.36	5.89	0.00	0.00	0.00
OB	12121.39	9776.78	2629.03	968.35	424.26	32.36	5.89	0.00	0.00	0.00
OC	12121.39	9776.78	2629.03	968.35	424.26	32.36	5.89	0.00	0.00	0.00
OD	12121.39	9776.78	2629.03	968.35	424.26	32.36	5.89	0.00	0.00	0.00



H[m]	D[m]	Max lux	Med lux	Alpha=9.4°+9.4°	G=0.0
1.00	0.33	12121	7632		
2.00	0.66	3030	1908		
3.00	0.99	1347	848		
4.00	1.32	758	477		
5.00	1.65	485	305		