

Luminaire

Code AD12604
Name PICTO 100 New led Verticale DIM Nero 4000K very wide flood

Measurem.


Code FTS1603590
Name PICTO 100 New led Verticale DIM Nero 4000K very wide flood

Luminaire Flux	2920.90 lm	Luminaire Power	35.00 W	Efficacy	83.45 lm/W	Efficiency	100.00%
Lamps Flux	2920.90 lm	Maximum value	995.88 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	100 mm 80 mm	Height Height	100 mm 0 mm		
Horizontal Luminous Area		0.005027 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.001216 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		2920.90 lm	
LED Flux=3606lm LED Power=31W Eff=81% EfcLed=116lm/W EfcLum=83lm/W Ra=90 SDCM=3 L70(6K)=50000h							
C.I.E.	84 94 99 100 100			D DIN 5040		A60	
F UTE	1.00 A			B NBN		BZ 1	

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.61	1.22	1.83	2.44	3.05	OC	0.61	1.22	1.83	2.44	3.05
OB	0.61	1.22	1.83	2.44	3.05	OD	0.61	1.22	1.83	2.44	3.05

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	2908.86	2772.55	2266.02	1767.55	1168.25	272.10	143.50	85.09	56.72	16.44
OB	2908.86	2772.55	2266.02	1767.55	1168.25	272.10	143.50	85.09	56.72	16.44
OC	2908.86	2772.55	2266.02	1767.55	1168.25	272.10	143.50	85.09	56.72	16.44
OD	2908.86	2772.55	2266.02	1767.55	1168.25	272.10	143.50	85.09	56.72	16.44



H[m]	D[m]	Max lux	Med lux	Alpha=31.4°+31.4°	G=0.0
1.00	1.22	2909	1352		
2.00	2.44	727	338		
3.00	3.67	323	150		
4.00	4.89	182	85		
5.00	6.11	116	54		

Luminaire

Code AD12604
Name PICTO 100 New led Verticale DIM Nero 4000K very wide flood

Measur.

Code FTS1603590
Name PICTO 100 New led Verticale DIM Nero 4000K very wide flood

Luminaire Flux	2920.90 lm	Luminaire Power	35.00 W	Efficacy	83.45 lm/W	Efficiency	100.00%
Lamps Flux	2920.90 lm	Maximum value	995.88 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	24.6	25.4	24.9	25.6	25.8	24.6	25.4	24.9	25.6	25.8
x=2H y=3H	25.2	25.9	25.5	26.2	26.4	25.2	25.9	25.5	26.2	26.4
x=2H y=4H	25.6	26.3	25.9	26.6	26.8	25.6	26.3	25.9	26.6	26.8
x=2H y=6H	26.0	26.6	26.3	26.9	27.2	26.0	26.6	26.3	26.9	27.2
x=2H y=8H	26.1	26.7	26.4	27.0	27.3	26.1	26.7	26.4	27.0	27.3
x=2H y=12H	26.2	26.8	26.5	27.1	27.4	26.2	26.8	26.5	27.1	27.4
x=4H y=2H	24.8	25.5	25.1	25.7	26.0	24.8	25.5	25.1	25.7	26.0
x=4H y=3H	25.6	26.2	26.0	26.5	26.8	25.6	26.2	26.0	26.5	26.8
x=4H y=4H	26.2	26.7	26.6	27.1	27.4	26.2	26.7	26.6	27.1	27.4
x=4H y=6H	26.7	27.2	27.1	27.5	27.9	26.7	27.2	27.1	27.5	27.9
x=4H y=8H	26.9	27.3	27.3	27.7	28.1	26.9	27.3	27.3	27.7	28.1
x=4H y=12H	27.1	27.4	27.5	27.8	28.2	27.1	27.4	27.5	27.8	28.2
x=8H y=4H	26.5	26.9	26.9	27.2	27.6	26.5	26.9	26.9	27.2	27.6
x=8H y=6H	27.1	27.4	27.6	27.9	28.3	27.1	27.4	27.6	27.9	28.3
x=8H y=8H	27.4	27.6	27.8	28.1	28.6	27.4	27.6	27.8	28.1	28.6
x=8H y=12H	27.6	27.8	28.1	28.3	28.8	27.6	27.8	28.1	28.3	28.8
x=12H y=4H	26.5	26.8	26.9	27.2	27.7	26.5	26.8	26.9	27.2	27.7
x=12H y=6H	27.2	27.4	27.6	27.9	28.4	27.2	27.4	27.6	27.9	28.4
x=12H y=8H	27.5	27.7	28.0	28.2	28.7	27.5	27.7	28.0	28.2	28.7