


Luminaire

Code 0761W10A+0772020A
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA TESSUTO NRO 360- 2700K

Measurem.

Code FTS1701400
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA TESSUTO NRO 360- 2700K

Luminaire Flux	1570.76 lm	Luminaire Power	31.00 W	Efficacy	50.67 lm/W	Efficiency	100.00%
Lamps Flux	1570.76 lm	Maximum value	487.71 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area	Diam. 360 mm Diam. 360 mm	Height	250 mm	Height	0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°	0.101788 m2 0.000000 m2 0.000000 m2	Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°	0.000000 m2 0.000000 m2 0.024625 m2				
Coordinate system	CG	Symmetry Type	Rotosymmetrical				
Date	21-09-2016	Maximum Gamma Angle	180				
Measurement Distance	0.00	Measurement Flux	1570.76 lm				
LED Flux=2722,9lm LED Power=25,6W Eff=58% EfcLed=106lm/W EfcLum=51lm/W Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E.	72 91 98 93 100	D DIN 5040	A61				
F UTE	0.93 B + 0.07 T	B NBN	BZ 2				



Luminaire

Code 0761W10A+0772020A
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA TESSUTO NRO 360- 2700K

Measur.


Code FTS1701400
 Name TOLOMEO MEGA LED BODY/DIMM + TOLOMEO MEGA TESSUTO NRO 360- 2700K

Luminaire Flux	1570.76 lm	Luminaire Power	31.00 W	Efficacy	50.67 lm/W	Efficiency	100.00%
Lamps Flux	1570.76 lm	Maximum value	487.71 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire Round Luminous Area		Diam. Diam.	360 mm 360 mm	Height Height	250 mm 0 mm		
Horizontal Luminous Area Emitting area on Plane 0° Emitting area on Plane 90°		0.101788 m2 0.000000 m2 0.000000 m2		Emitting area on Plane 180° Emitting area on Plane 270° Glare area at 76°		0.000000 m2 0.000000 m2 0.024625 m2	
Coordinate system Date Measurement Distance		CG 21-09-2016 0.00		Symmetry Type Maximum Gamma Angle Measurement Flux		Rotosymmetrical 180 1570.76 lm	
LED Flux=2722,9lm LED Power=25,6W Eff=58% EfcLed=106lm/W EfcLum=51lm/W Ra=90 SDCM=2 L70(6K)=50000h							
C.I.E. F UTE	72 91 98 93 100 0.93 B + 0.07 T			D DIN 5040 B NBN		A61 BZ 2	

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.90	1.80	2.71	3.61	4.51	OC	0.90	1.80	2.71	3.61	4.51
OB	0.90	1.80	2.71	3.61	4.51	OD	0.90	1.80	2.71	3.61	4.51

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	766.08	763.49	758.93	716.94	643.24	201.00	131.19	83.89	40.89	10.02
OB	766.08	763.49	758.93	716.94	643.24	201.00	131.19	83.89	40.89	10.02
OC	766.08	763.49	758.93	716.94	643.24	201.00	131.19	83.89	40.89	10.02
OD	766.08	763.49	758.93	716.94	643.24	201.00	131.19	83.89	40.89	10.02



H[m]	D[m]	Max lux	Med lux	Alpha=42.1°+42.1°	G=0.0
1.00	1.80	766	345		
2.00	3.61	192	86		
3.00	5.41	85	38		
4.00	7.22	48	22		
5.00	9.02	31	14		