

Luminaire


Code AG00104
Name SMARTOFFICE SUSPENSION DIR + IND 1129mm 940 DARKLIGHT N/D BLACK

Measurem.

Code FTS1603407
Name SMARTOFFICE SUSPENSION DIR + IND 1129mm 940 DARKLIGHT N/D BLACK

Luminaire Flux	4564.00 lm	Luminaire Power	37.00 W	Efficacy	123.35 lm/W	Efficiency	100.00%
Lamps Flux	4564.00 lm	Maximum value	329.16 cd/klm	Position	C=50.00 G=4.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1130 mm	Width	65 mm	Height	90 mm
Rectangular Luminous Area		Length	1080 mm	Width	55 mm	Height	0 mm
Horizontal Luminous Area		0.059400 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.014370 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		26-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4564.00 lm	
LED Flux=6000lm LED Power=33,3W Eff=76% EfcLed=180lm/W EfcLum=123lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	70 99 100 63 100			D DIN 5040	B51		
F UTE	0.63 C + 0.37 T			B NBN	BZ 2		

1130mm x 65mm




Semipiani C

180.0 ——— 0.0
270.0 - - - - 90.0

ULOR 37.05 %

DLOR 62.95 %

RN 37.05 %



Luminaire

Code AG00104
Name SMARTOFFICE SUSPENSION DIR + IND 1129mm 940 DARKLIGHT N/D BLACK

Measur.


Code FTS1603407
Name SMARTOFFICE SUSPENSION DIR + IND 1129mm 940 DARKLIGHT N/D BLACK

Luminaire Flux	4564.00 lm	Luminaire Power	37.00 W	Efficacy	123.35 lm/W	Efficiency	100.00%
Lamps Flux	4564.00 lm	Maximum value	329.16 cd/klm	Position	C=50.00 G=4.00	CG	Double Symmetrical
Rectangular Luminaire		Length	1130 mm	Width	65 mm	Height	90 mm
Rectangular Luminous Area		Length	1080 mm	Width	55 mm	Height	0 mm
Horizontal Luminous Area		0.059400 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.014370 m2	
Coordinate system		CG		Symmetry Type		Double Symmetrical	
Date		26-04-2017		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		4564.00 lm	
LED Flux=6000lm LED Power=33,3W Eff=76% EfcLed=180lm/W EfcLum=123lm/W Ra=80 SDCM=3 L70(6K)=50000h							
C.I.E.	70 99 100 63 100			D DIN 5040	B51		
F UTE	0.63 C + 0.37 T			B NBN	BZ 2		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	1.13	2.26	3.39	4.53	5.66	OC	1.19	2.38	3.56	4.75	5.94
OB	1.13	2.26	3.39	4.53	5.66	OD	1.19	2.38	3.56	4.75	5.94

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	1501.03	1500.37	1472.60	1377.26	1202.21	909.75	270.49	13.97	9.51	7.37
OB	1501.03	1500.37	1472.60	1377.26	1202.21	909.75	270.49	13.97	9.51	7.37
OC	1501.03	1501.05	1438.29	1286.15	1095.28	878.80	103.60	13.54	7.34	5.29
OD	1501.03	1501.05	1438.29	1286.15	1095.28	878.80	103.60	13.54	7.34	5.29



H[m]	D[m]	Max lux	Med lux	Alpha=48.5°+48.5°	G=0.0
1.00	2.26	1501	489		
2.00	4.53	375	122		
3.00	6.79	167	54		
4.00	9.05	94	31		
5.00	11.31	60	20		

H[m]	D[m]	Max lux	Med lux	Beta=49.9°+49.9°	G=0.0
1.00	2.38	1501	489		
2.00	4.75	375	122		
3.00	7.13	167	54		
4.00	9.50	94	31		
5.00	11.88	60	20		

Luminaire

Code AG00104
Name SMARTOFFICE SUSPENSION DIR + IND 1129mm 940 DARKLIGHT N/D BLACK

Measur.

Code FTS1603407
Name SMARTOFFICE SUSPENSION DIR + IND 1129mm 940 DARKLIGHT N/D BLACK

Luminaire Flux	4564.00 lm	Luminaire Power	37.00 W	Efficacy	123.35 lm/W	Efficiency	100.00%
Lamps Flux	4564.00 lm	Maximum value	329.16 cd/klm	Position	C=50.00 G=4.00	CG	Double Symmetrical

UGR
S = 0.250

Reflectancies										
Ceiling/Cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
WorkingPlane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
RoomDimensions	ViewedCrosswise					ViewedEndwise				
x=2H y=2H	17.6	18.4	18.3	19.1	19.9	17.6	18.3	18.3	19.1	19.9
x=2H y=3H	17.4	18.0	18.1	18.8	19.7	17.3	18.0	18.1	18.7	19.7
x=2H y=4H	17.2	17.8	18.0	18.6	19.5	17.2	17.8	18.0	18.6	19.5
x=2H y=6H	17.1	17.7	17.9	18.5	19.4	17.1	17.6	17.9	18.4	19.4
x=2H y=8H	17.1	17.6	17.9	18.4	19.3	17.0	17.5	17.8	18.3	19.3
x=2H y=12H	17.0	17.5	17.8	18.3	19.3	17.0	17.5	17.8	18.3	19.3
x=4H y=2H	17.3	17.9	18.1	18.7	19.6	17.3	17.9	18.1	18.7	19.6
x=4H y=3H	17.1	17.6	17.9	18.4	19.4	17.0	17.5	17.9	18.4	19.4
x=4H y=4H	17.0	17.4	17.8	18.2	19.2	16.9	17.3	17.8	18.2	19.2
x=4H y=6H	16.8	17.2	17.7	18.1	19.1	16.8	17.2	17.7	18.0	19.1
x=4H y=8H	16.8	17.1	17.7	18.0	19.0	16.7	17.1	17.6	17.9	19.0
x=4H y=12H	16.7	17.0	17.6	17.9	18.9	16.6	17.0	17.6	17.8	18.9
x=8H y=4H	16.7	17.1	17.6	18.0	19.0	16.7	17.0	17.6	17.9	19.0
x=8H y=6H	16.6	16.9	17.5	17.8	18.9	16.6	16.8	17.5	17.8	18.9
x=8H y=8H	16.6	16.8	17.5	17.7	18.8	16.5	16.8	17.4	17.7	18.8
x=8H y=12H	16.5	16.7	17.5	17.7	18.7	16.5	16.7	17.4	17.6	18.7
x=12H y=4H	16.7	17.0	17.6	17.9	18.9	16.6	16.9	17.5	17.8	18.9
x=12H y=6H	16.6	16.8	17.5	17.7	18.8	16.5	16.7	17.4	17.7	18.8
x=12H y=8H	16.5	16.7	17.4	17.6	18.7	16.4	16.7	17.4	17.6	18.7