

## Luminaire

Code AN30604+M282007  
 Name VECTOR 95 TRACK 930 SP DALI EUTRAC NRO + lens for elliptical emission

## Measurem.

Code FTS1901595  
 Name VECTOR 95 TRACK 930 SP DALI EUTRAC NRO + lens for elliptical emission

|  |   |   |   |          |               |            |                    |
|--|---|---|---|----------|---------------|------------|--------------------|
| Luminaire Flux   | 1734.53 lm                                | Luminaire Power   | 30.00 W                                   | Efficacy | 57.82 lm/W    | Efficiency | 100.00%            |
| Lamps Flux   | 1734.53 lm                                | Maximum value   | 3833.21 cd/klm                            | Position | C=0.00 G=0.00 | CG         | Double Symmetrical |
| Round Luminaire<br>Round Luminous Area   | Diam. 95 mm<br>Diam. 75 mm                | Height  | 210 mm                                    | Height   | 0 mm          |            |                    |
| Horizontal Luminous Area<br>Emitting area on Plane 0°<br>Emitting area on Plane 90°                        | 0.004418 m2<br>0.000000 m2<br>0.000000 m2 | Emitting area on Plane 180°<br>Emitting area on Plane 270°<br>Glare area at 76° | 0.000000 m2<br>0.000000 m2<br>0.001069 m2 |          |               |            |                    |
| Coordinate system  | CG  | Symmetry Type   | Double Symmetrical                        |          |               |            |                    |
| Date   | 29-03-2019                                | Maximum Gamma Angle   | 180                                       |          |               |            |                    |
| Measurement Distance   | 0.00                                      | Measurement Flux  | 1734.53 lm                                |          |               |            |                    |
| LED Flux=3432lm LED Power=27.5W Eff=51% EfcLed=125lm/W EfcLum=58lm/W CCT=3000K Ra=90 SDCM=3 L70(6K)=50000h |   |   |   |          |               |            |                    |
| C.I.E.   | 96 99 100 100 100                         | D DIN 5040  | A60                                       |          |               |            |                    |
| F UTE  | 1.00 A                                    | B NBN   | BZ 1                                      |          |               |            |                    |



