

Luminaire

Code AN11201+AP91300
Name VECTOR 55 TRACK 927 FL ND BCO + SOFT FILTER

Measurem.

Code FTS2001499-A
Name VECTOR 55 TRACK 927 FL ND BCO + SOFT FILTER

Luminaire Flux	1320 lm	Luminaire Power	25.0 W	Efficacy	52.812 lm/W	Efficiency	100.00%
Source Flux	1320 lm	Maximum value	3862.92 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-10-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1320 lm	
LED Flux=2254lm LED Power=21W Eff=59% EfcLed=107lm/W EfcLum=53lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	98 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Diam=55mm




Semipiani C

180.0 ——— 0.0

ULOR 0.00 %

DLOR100.00 %

RN 0.00 %



Luminaire

Code AN11201+AP91300
Name VECTOR 55 TRACK 927 FL ND BCO + SOFT FILTER

Measurem.


Code FTS2001499-A
Name VECTOR 55 TRACK 927 FL ND BCO + SOFT FILTER

Luminaire Flux	1320 lm	Luminaire Power	25.0 W	Efficacy	52.812 lm/W	Efficiency	100.00%
Source Flux	1320 lm	Maximum value	3862.92 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical
Round Luminaire		Diam.	55 mm	Height	130 mm		
Round Luminous Area		Diam.	46 mm	Height	0 mm		
Horizontal Luminous Area		0.001662 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.000402 m2	
Coordinate system		CG		Symmetry Type		Rotosymmetrical	
Date		20-10-2021		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		1320 lm	
LED Flux=2254lm LED Power=21W Eff=59% EfcLed=107lm/W EfcLum=53lm/W CCT=2700K Ra=90 R9=50 SDCM=3 L70(6K)=50000h							
C.I.E.	98 99 100 100 100			D DIN 5040	A60		
F UTE	--			B NBN	BZ 1		

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.23	0.46	0.69	0.92	1.16	OC	0.23	0.46	0.69	0.92	1.16
OB	0.23	0.46	0.69	0.92	1.16	OD	0.23	0.46	0.69	0.92	1.16

	Luminous Intensities [cd/klm]									
	0	5	15	25	35	45	55	65	75	85
OA	5100.21	4590.53	2058.13	523.70	99.56	20.84	7.58	5.41	3.36	0.77
OB	5100.21	4590.53	2058.13	523.70	99.56	20.84	7.58	5.41	3.36	0.77
OC	5100.21	4590.53	2058.13	523.70	99.56	20.84	7.58	5.41	3.36	0.77
OD	5100.21	4590.53	2058.13	523.70	99.56	20.84	7.58	5.41	3.36	0.77



H[m]	D[m]	Max lux	Med lux	Alpha=13.0°+13.0°	G=0.0
1.00	0.46	5100	3165		
2.00	0.92	1275	791		
3.00	1.39	567	352		
4.00	1.85	319	198		
5.00	2.31	204	127		