
Luminaire
Code AP53320
Name VECTOR 55 RECESSED 927 WF BR.BRONZE
Measurem.
Code FTS1900897
Name VECTOR 55 RECESSED 927 WF BR.BRONZE

Luminaire Flux	1435 lm	Luminaire Power	17.5 W	Efficacy	82.023 lm/W	Efficiency	100.00%
Source Flux	1435 lm	Maximum value	3574.81 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical


Round Luminaire	Diam. 55 mm	Height	130 mm
Round Luminous Area	Diam. 46 mm	Height	0 mm
Horizontal Luminous Area	0.001662 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000402 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	07-09-2021	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	1435 lm

LED Flux=1885lm LED Power=17.5W Eff=76% EfcLed=108lm/W EfcLum=82lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	99 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1



Diam=55mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code AP53320
Name VECTOR 55 RECESSED 927 WF BR.BRONZE
Measurem.
Code FTS1900897
Name VECTOR 55 RECESSED 927 WF BR.BRONZE

Luminaire Flux	1435 lm	Luminaire Power	17.5 W	Efficacy	82.023 lm/W	Efficiency	100.00%
Source Flux	1435 lm	Maximum value	3574.81 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 55 mm	Height	130 mm
Round Luminous Area	Diam. 46 mm	Height	0 mm
Horizontal Luminous Area	0.001662 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000402 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	07-09-2021	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	1435 lm

LED Flux=1885lm LED Power=17.5W Eff=76% EfcLed=108lm/W EfcLum=82lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	99 100 100 100 100	D DIN 5040	A60
F UTE	--	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.27	0.55	0.82	1.10	1.37	OC	0.27	0.55	0.82	1.10	1.37
OB	0.27	0.55	0.82	1.10	1.37	OD	0.27	0.55	0.82	1.10	1.37

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	5131.32	4899.35	2668.45	514.98	13.91	4.91	2.69	1.93	1.17	0.43
OB	5131.32	4899.35	2668.45	514.98	13.91	4.91	2.69	1.93	1.17	0.43
OC	5131.32	4899.35	2668.45	514.98	13.91	4.91	2.69	1.93	1.17	0.43
OD	5131.32	4899.35	2668.45	514.98	13.91	4.91	2.69	1.93	1.17	0.43



H[m]	D[m]	Max lux	Med lux	Alpha=15.3°+15.3°	G=0.0
1.00	0.55	5131	3241		
2.00	1.10	1283	810		
3.00	1.65	570	360		
4.00	2.19	321	203		
5.00	2.74	205	130		