
Luminaire
Code AP11418_MIN
Name VECTOR 55 MAGNET ZOOM 927 DALI BR.COPPER - MIN
Measurem.
Code FTS1801628
Name VECTOR 55 MAGNET ZOOM 927 DALI BR.COPPER - MIN

Luminaire Flux	634 lm	Luminaire Power	20.5 W	Efficacy	30.919 lm/W	Efficiency	100.00%
Source Flux	634 lm	Maximum value	5139.89 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical


Round Luminaire	Diam. 55 mm	Height	130 mm
Round Luminous Area	Diam. 44 mm	Height	0 mm
Horizontal Luminous Area	0.001521 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000368 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	27-09-2021	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	634 lm

LED Flux=2044lm LED Power=19.4W Eff=31% EfcLed=105lm/W EfcLum=31lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h

C.I.E.	96 99 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1



Diam=55mm



Semipiani C

180.0 0.0

ULOR 0.00 %
DLOR100.00 %
RN 0.00 %

Luminaire
Code AP11418_MIN
Name VECTOR 55 MAGNET ZOOM 927 DALI BR.COPPER - MIN
Measurem.
Code FTS1801628
Name VECTOR 55 MAGNET ZOOM 927 DALI BR.COPPER - MIN

Luminaire Flux	634 lm	Luminaire Power	20.5 W	Efficacy	30.919 lm/W	Efficiency	100.00%
Source Flux	634 lm	Maximum value	5139.89 cd/klm	Position	C=0.00 G=0.00	CG	Rotosymmetrical

Round Luminaire	Diam. 55 mm	Height	130 mm
Round Luminous Area	Diam. 44 mm	Height	0 mm
Horizontal Luminous Area	0.001521 m2	Emitting area on Plane 180°	0.000000 m2
Emitting area on Plane 0°	0.000000 m2	Emitting area on Plane 270°	0.000000 m2
Emitting area on Plane 90°	0.000000 m2	Glare area at 76°	0.000368 m2
Coordinate system	CG	Symmetry Type	Rotosymmetrical
Date	27-09-2021	Maximum Gamma Angle	180
Measurement Distance	0.00	Measurement Flux	634 lm

LED Flux=2044lm LED Power=19.4W Eff=31% EfcLed=105lm/W EfcLum=31lm/W CCT=2700K Ra=90 SDCM=3 L70(6K)=50000h


C.I.E.	96 99 100 100 100	D DIN 5040	A60
F UTE	1.00 A	B NBN	BZ 1

Width at 50.00 % of Max Intensity

H[m]	1.00	2.00	3.00	4.00	5.00	H[m]	1.00	2.00	3.00	4.00	5.00
OA	0.20	0.39	0.59	0.79	0.98	OC	0.20	0.39	0.59	0.79	0.98
OB	0.20	0.39	0.59	0.79	0.98	OD	0.20	0.39	0.59	0.79	0.98

Luminous Intensities [cd/klm]

	0	5	15	25	35	45	55	65	75	85
OA	3257.87	2815.64	946.66	157.29	33.78	16.57	10.09	5.16	1.70	0.11
OB	3257.87	2815.64	946.66	157.29	33.78	16.57	10.09	5.16	1.70	0.11
OC	3257.87	2815.64	946.66	157.29	33.78	16.57	10.09	5.16	1.70	0.11
OD	3257.87	2815.64	946.66	157.29	33.78	16.57	10.09	5.16	1.70	0.11



H[m]	D[m]	Max lux	Med lux	Alpha=11.1°+11.1° G=0.0
1.00	0.39	3258	2043	
2.00	0.79	814	511	
3.00	1.18	362	227	
4.00	1.57	204	128	
5.00	1.97	130	82	